




circuit breaker VL160H high breaking capacity Icu=70kA, 415V AC 3-pole, line protection Trip Unit TM, LI In=100A, rated current IR=80...100A, overload protection, II=500...1000A, short-circuit protection Shunt release 110...127 V AC Auxiliary switch mounting kit 2 AUX (1 NO + 1 NC)

Weight	2.2 kg
Net Weight	2.2 kg

### Approvals / Certificates

Environment	General Product Approval				
<a href="#">Environmental Conformations</a>	<a href="#">Environmental Conformations</a>			<a href="#">Confirmation</a>	

Test Certificates	other				
<a href="#">Special Test Certificate</a>	<a href="#">Miscellaneous</a>	<a href="#">Confirmation</a>	<a href="#">Miscellaneous</a>		

### Further information

- Information on the packaging  
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
- Information for data generation and storage  
<https://support.industry.siemens.com/cs/ww/en/view/109995012>
- Information- and Downloadcenter (catalogues, leaflets,...)  
<https://www.siemens.com/energy-automation>
- Industry Mall (Online ordering system)  
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL2710-2DC33-8RB1>
- Service&Support (Manuals, Certificates, Characteristics, FAQs,...)  
<https://support.industry.siemens.com/cs/ww/en/ps/3VL2710-2DC33-8RB1>
- Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)  
[https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VL2710-2DC33-8RB1](https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL2710-2DC33-8RB1)
- CAX-Online-Generator  
<https://www.siemens.com/cax>
- Characteristic curves  
[https://curves.simaris.siemens.com/curves/<mmp\\_prod\\_noCOMP="HAUPT"></mmp\\_prod\\_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)



last modified:

3/10/2026 

