




circuit breaker VL160N standard breaking capacity Icu=55kA, 415V AC 3-pole, line protection Trip Unit TM, LI In=125A, rated current IR=100...125A, overload protection, II=625...1250A, short-circuit protection Undervoltage release 220...250 V AC Auxiliary/alarm switch mounting kit 2 AUX (1 NO+1 NC)+1 AS (1 NO)

Weight	2.2 kg
Net Weight	2.2 kg

Approvals / Certificates

Environment	General Product Approval				
Environmental Conformations	Environmental Conformations			Confirmation	

Test Certificates

Test Certificates	other				
Special Test Certificate	Miscellaneous	Confirmation		Miscellaneous	

Further information

- Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
- Information for data generation and storage
<https://support.industry.siemens.com/cs/ww/en/view/109995012>
- Information- and Downloadcenter (catalogues, leaflets,...)
<https://www.siemens.com/energy-automation>
- Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL2712-1DC33-2HD1>
- Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/3VL2712-1DC33-2HD1>
- Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL2712-1DC33-2HD1
- CAX-Online-Generator
<https://www.siemens.com/cax>
- Characteristic curves
[https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP="HAUPT"></mmp_prod_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)



last modified: 3/10/2026 

