




circuit breaker VL250N standard breaking capacity Icu=55kA, 415V AC 4-pole, line protection trip unit, TM, LI In=200A, rated current IR=160...200A, overload prot. II=1000...2000A, short-circuit protection N protected (100%) without auxiliary release without auxiliary/alarm switch, spare part product only for replacement purposes

Weight	3.2 kg
Net Weight	3.2 kg

Approvals / Certificates

Environment	General Product Approval				
Environmental Confirmations	Environmental Confirmations			Confirmation	

Test Certificates	other				
Special Test Certificate	Miscellaneous	Confirmation	Miscellaneous		

Further information

- Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
- Information for data generation and storage
<https://support.industry.siemens.com/cs/ww/en/view/109995012>
- Information- and Downloadcenter (catalogues, leaflets,...)
<https://www.siemens.com/energy-automation>
- Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL3720-1EM46-0AA0>
- Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/3VL3720-1EM46-0AA0>
- Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL3720-1EM46-0AA0
- CAx-Online-Generator
<https://www.siemens.com/cax>
- Characteristic curves
[https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP="HAUPT"></mmp_prod_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)



last modified:

11/24/2025 

