

Crimp contact - CDC-MP 0,14-0,5-R - 1016663

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Crimp contact

RoHS

Key Commercial Data

Packing unit	5000 pc
Minimum order quantity	5000 pc
GTIN	 4 055626 498430
GTIN	4055626498430
Weight per Piece (excluding packing)	0.120 g
Custom tariff number	85366990
Note	Made to Order (non-returnable)

Technical data

Dimensions for the product

Pitch	0 mm
-------	------

Packaging information

Type of packaging	Belt
Pieces per package	5000
Denomination packing units	Pcs.

General product information

Type of note	Note on application
	Order information:
	Note regarding documentation
Note	The crimp contacts may only be processed with approved crimping tools.
	You can find ordering information for the approved crimping tool for automated conductor connections in the installation instructions in the Downloads section.

Crimp contact - CDC-MP 0,14-0,5-R - 1016663

Technical data

General product information

	The crimp heights depend on the crimping tool used. You can find the values in the tool documentation.
--	--

Classifications

eCl@ss

eCl@ss 4.0	27260700
eCl@ss 4.1	27260700
eCl@ss 5.0	27260700
eCl@ss 5.1	27260700
eCl@ss 6.0	27260700
eCl@ss 7.0	27440309
eCl@ss 8.0	27440204
eCl@ss 9.0	27440204

ETIM

ETIM 5.0	EC000796
ETIM 6.0	EC002638
ETIM 7.0	EC002638

Accessories

Additional products

PCB direct plug - CDDC 1,5/ 2-PV-3,5 - 1016515



PCB direct plug, nominal current: 8 A, rated voltage (III/2): 160 V, nominal cross section: 1.5 mm², number of positions: 2, pitch: 3.5 mm, connection method: Crimp connection, color: green, contact surface: Tin, mounting: SKEDD - Direct plug-in technology, pin layout: Linear pinning

PCB direct plug - CDDC 1,5/ 3-PV-3,5 - 1016513



PCB direct plug, nominal current: 8 A, rated voltage (III/2): 160 V, nominal cross section: 1.5 mm², number of positions: 3, pitch: 3.5 mm, connection method: Crimp connection, color: green, contact surface: Tin, mounting: SKEDD - Direct plug-in technology, pin layout: Linear pinning

Crimp contact - CDC-MP 0,14-0,5-R - 1016663

Accessories

PCB direct plug - CDDC 1,5/ 4-PV-3,5 - 1016512



PCB direct plug, nominal current: 8 A, rated voltage (III/2): 160 V, nominal cross section: 1.5 mm², number of positions: 4, pitch: 3.5 mm, connection method: Crimp connection, color: green, contact surface: Tin, mounting: SKEDD - Direct plug-in technology, pin layout: Linear pinning

PCB direct plug - CDDC 1,5/ 5-PV-3,5 - 1016516



PCB direct plug, nominal current: 8 A, rated voltage (III/2): 160 V, nominal cross section: 1.5 mm², number of positions: 5, pitch: 3.5 mm, connection method: Crimp connection, color: green, contact surface: Tin, mounting: SKEDD - Direct plug-in technology, pin layout: Linear pinning

PCB direct plug - CDDC 1,5/ 6-PV-3,5 - 1016517




PCB direct plug, nominal current: 8 A, rated voltage (III/2): 160 V, nominal cross section: 1.5 mm², number of positions: 6, pitch: 3.5 mm, connection method: Crimp connection, color: green, contact surface: Tin, mounting: SKEDD - Direct plug-in technology, pin layout: Linear pinning

PCB direct plug - CDDC 1,5/ 7-PV-3,5 - 1016518



PCB direct plug, nominal current: 8 A, rated voltage (III/2): 160 V, nominal cross section: 1.5 mm², number of positions: 7, pitch: 3.5 mm, connection method: Crimp connection, color: green, contact surface: Tin, mounting: SKEDD - Direct plug-in technology, pin layout: Linear pinning

PCB direct plug - CDDC 1,5/ 8-PV-3,5 - 1016519



PCB direct plug, nominal current: 8 A, rated voltage (III/2): 160 V, nominal cross section: 1.5 mm², number of positions: 8, pitch: 3.5 mm, connection method: Crimp connection, color: green, contact surface: Tin, mounting: SKEDD - Direct plug-in technology, pin layout: Linear pinning

Crimp contact - CDC-MP 0,14-0,5-R - 1016663

Accessories

PCB direct plug - CDDC 1,5/ 9-PV-3,5 - 1016520



PCB direct plug, nominal current: 8 A, rated voltage (III/2): 160 V, nominal cross section: 1.5 mm², number of positions: 9, pitch: 3.5 mm, connection method: Crimp connection, color: green, contact surface: Tin, mounting: SKEDD - Direct plug-in technology, pin layout: Linear pinning

PCB direct plug - CDDC 1,5/10-PV-3,5 - 1016521



PCB direct plug, nominal current: 8 A, rated voltage (III/2): 160 V, nominal cross section: 1.5 mm², number of positions: 10, pitch: 3.5 mm, connection method: Crimp connection, color: green, contact surface: Tin, mounting: SKEDD - Direct plug-in technology, pin layout: Linear pinning

PCB direct plug - CDDC 1,5/11-PV-3,5 - 1016510




PCB direct plug, nominal current: 8 A, rated voltage (III/2): 160 V, nominal cross section: 1.5 mm², number of positions: 11, pitch: 3.5 mm, connection method: Crimp connection, color: green, contact surface: Tin, mounting: SKEDD - Direct plug-in technology, pin layout: Linear pinning

PCB direct plug - CDDC 1,5/12-PV-3,5 - 1016522



PCB direct plug, nominal current: 8 A, rated voltage (III/2): 160 V, nominal cross section: 1.5 mm², number of positions: 12, pitch: 3.5 mm, connection method: Crimp connection, color: green, contact surface: Tin, mounting: SKEDD - Direct plug-in technology, pin layout: Linear pinning

PCB direct plug - CDDC 1,5/13-PV-3,5 - 1016523



PCB direct plug, nominal current: 8 A, rated voltage (III/2): 160 V, nominal cross section: 1.5 mm², number of positions: 13, pitch: 3.5 mm, connection method: Crimp connection, color: green, contact surface: Tin, mounting: SKEDD - Direct plug-in technology, pin layout: Linear pinning

Crimp contact - CDC-MP 0,14-0,5-R - 1016663

Accessories

PCB direct plug - CDDC 1,5/14-PV-3,5 - 1016524



PCB direct plug, nominal current: 8 A, rated voltage (III/2): 160 V, nominal cross section: 1.5 mm², number of positions: 14, pitch: 3.5 mm, connection method: Crimp connection, color: green, contact surface: Tin, mounting: SKEDD - Direct plug-in technology, pin layout: Linear pinning

PCB direct plug - CDDC 1,5/15-PV-3,5 - 1016525



PCB direct plug, nominal current: 8 A, rated voltage (III/2): 160 V, nominal cross section: 1.5 mm², number of positions: 15, pitch: 3.5 mm, connection method: Crimp connection, color: green, contact surface: Tin, mounting: SKEDD - Direct plug-in technology, pin layout: Linear pinning

PCB direct plug - CDDC 1,5/16-PV-3,5 - 1016526



PCB direct plug, nominal current: 8 A, rated voltage (III/2): 160 V, nominal cross section: 1.5 mm², number of positions: 16, pitch: 3.5 mm, connection method: Crimp connection, color: green, contact surface: Tin, mounting: SKEDD - Direct plug-in technology, pin layout: Linear pinning

Direct connector - CDDC 2,5/ 2-PV-5,0 - 1016293



PCB direct plug, nominal current: 12 A, rated voltage (III/2): 320 V, nominal cross section: 2.5 mm², number of positions: 2, pitch: 5 mm, connection method: Crimp connection, color: green, contact surface: Tin, mounting: SKEDD - Direct plug-in technology, pin layout: Linear pinning

Direct connector - CDDC 2,5/ 3-PV-5,0 - 1016292



PCB direct plug, nominal current: 12 A, rated voltage (III/2): 320 V, nominal cross section: 2.5 mm², number of positions: 3, pitch: 5 mm, connection method: Crimp connection, color: green, contact surface: Tin, mounting: SKEDD - Direct plug-in technology, pin layout: Linear pinning

Crimp contact - CDC-MP 0,14-0,5-R - 1016663

Accessories

Direct connector - CDDC 2,5/ 4-PV-5,0 - 1016290



PCB direct plug, nominal current: 12 A, rated voltage (III/2): 320 V, nominal cross section: 2.5 mm², number of positions: 4, pitch: 5 mm, connection method: Crimp connection, color: green, contact surface: Tin, mounting: SKEDD
- Direct plug-in technology, pin layout: Linear pinning

Direct connector - CDDC 2,5/ 5-PV-5,0 - 1016289



PCB direct plug, nominal current: 12 A, rated voltage (III/2): 320 V, nominal cross section: 2.5 mm², number of positions: 5, pitch: 5 mm, connection method: Crimp connection, color: green, contact surface: Tin, mounting: SKEDD
- Direct plug-in technology, pin layout: Linear pinning

Direct connector - CDDC 2,5/ 6-PV-5,0 - 1016288



PCB direct plug, nominal current: 12 A, rated voltage (III/2): 320 V, nominal cross section: 2.5 mm², number of positions: 6, pitch: 5 mm, connection method: Crimp connection, color: green, contact surface: Tin, mounting: SKEDD
- Direct plug-in technology, pin layout: Linear pinning

Direct connector - CDDC 2,5/ 7-PV-5,0 - 1016286



PCB direct plug, nominal current: 12 A, rated voltage (III/2): 320 V, nominal cross section: 2.5 mm², number of positions: 7, pitch: 5 mm, connection method: Crimp connection, color: green, contact surface: Tin, mounting: SKEDD
- Direct plug-in technology, pin layout: Linear pinning

Direct connector - CDDC 2,5/ 8-PV-5,0 - 1016285



PCB direct plug, nominal current: 12 A, rated voltage (III/2): 320 V, nominal cross section: 2.5 mm², number of positions: 8, pitch: 5 mm, connection method: Crimp connection, color: green, contact surface: Tin, mounting: SKEDD
- Direct plug-in technology

Crimp contact - CDC-MP 0,14-0,5-R - 1016663

Accessories

Direct connector - CDDC 2,5/ 9-PV-5,0 - 1016280



PCB direct plug, nominal current: 12 A, rated voltage (III/2): 320 V, nominal cross section: 2.5 mm², number of positions: 9, pitch: 5 mm, connection method: Crimp connection, color: green, contact surface: Tin, mounting: SKEDD - Direct plug-in technology

PCB direct plug - CDDC 2,5/10-PV-5,0 - 1016279



PCB direct plug, nominal current: 12 A, rated voltage (III/2): 320 V, nominal cross section: 2.5 mm², number of positions: 10, pitch: 5 mm, connection method: Crimp connection, color: green, contact surface: Tin, mounting: SKEDD - Direct plug-in technology

PCB direct plug - CDDC 2,5/11-PV-5,0 - 1016278



PCB direct plug, nominal current: 12 A, rated voltage (III/2): 320 V, nominal cross section: 2.5 mm², number of positions: 11, pitch: 5 mm, connection method: Crimp connection, color: green, contact surface: Tin, mounting: SKEDD - Direct plug-in technology

PCB direct plug - CDDC 2,5/12-PV-5,0 - 1016277



PCB direct plug, nominal current: 12 A, rated voltage (III/2): 320 V, nominal cross section: 2.5 mm², number of positions: 12, pitch: 5 mm, connection method: Crimp connection, color: green, contact surface: Tin, mounting: SKEDD - Direct plug-in technology

PCB direct plug - CDDC 2,5/13-PV-5,0 - 1016276



PCB direct plug, nominal current: 12 A, rated voltage (III/2): 320 V, nominal cross section: 2.5 mm², number of positions: 13, pitch: 5 mm, connection method: Crimp connection, color: green, contact surface: Tin, mounting: SKEDD - Direct plug-in technology

Crimp contact - CDC-MP 0,14-0,5-R - 1016663

Accessories

PCB direct plug - CDDC 2,5/14-PV-5,0 - 1016274



PCB direct plug, nominal current: 12 A, rated voltage (III/2): 320 V, nominal cross section: 2.5 mm², number of positions: 14, pitch: 5 mm, connection method: Crimp connection, color: green, contact surface: Tin, mounting: SKEDD - Direct plug-in technology

PCB direct plug - CDDC 2,5/15-PV-5,0 - 1016273



PCB direct plug, nominal current: 12 A, rated voltage (III/2): 320 V, nominal cross section: 2.5 mm², number of positions: 15, pitch: 5 mm, connection method: Crimp connection, color: green, contact surface: Tin, mounting: SKEDD - Direct plug-in technology

PCB direct plug - CDDC 2,5/16-PV-5,0 - 1016272



PCB direct plug, nominal current: 12 A, rated voltage (III/2): 320 V, nominal cross section: 2.5 mm², number of positions: 16, pitch: 5 mm, connection method: Crimp connection, color: green, contact surface: Tin, mounting: SKEDD - Direct plug-in technology