



SENTRON, cylindrical fuse link, 8x32 mm, 20 A, gG, Un AC: 400 V

Figure similar

Model	
product brand name	SENTRON
product designation	Cylindrical fuse link
General technical data	
operating class of the fuse link	gG
type of voltage of the operating voltage	AC
Dissipation	
power loss [W]	1.7 W
power loss [W] for rated value of the current at AC in hot operating state per pole	2 W
Main circuit	
operational current rated value	20 A
Product details	
product component striker	No
Mechanical Design	
mounting position	Any, preferably vertical
Net Weight	4 g
Approvals Certificates	
Environment	General Product Approval

[Environmental Confirmations](#)

[Environmental Confirmations](#)



[Confirmation](#)



other

[Confirmation](#)



Further information

Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
 Information for data generation and storage
<https://support.industry.siemens.com/cs/ww/en/view/109995012>
 Information- and Downloadcenter (Catalogs, Brochures,...)
<https://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NW6307-1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NW6307-1>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NW6307-1

CAX-Online-Generator



<https://www.siemens.com/cax>

Tender specifications

<https://www.siemens.com/specifications>

Characteristic curves

https://curves.simarisiemens.com/curves/<mmp_prod_noCOMP='HAUPT'></mmp_prod_no>



last modified:

4/11/2025 

