



undervoltage release 400 V AC/50 Hz with leading auxiliary contact 2 NO with spring-loaded terminal for 3RV2 motor starter protector/circuit breaker

<b>product brand name</b>	SIRIUS
<b>product category</b>	Auxiliary release
<b>product designation</b>	undervoltage release
<b>design of the product</b>	with 2 auxiliary contacts
<b>product type designation</b>	3RV29
<b>suitability for use</b>	motor circuit breaker
<b>General technical data</b>	
<b>certificate of suitability</b>	CE / UL / CSA
<b>size of the circuit-breaker</b>	S00, S0, S2, S3
<b>closing active power at AC maximum</b>	13 W
<b>active power at AC in operation maximum</b>	2.4 W
<b>apparent power at AC in operation maximum</b>	7.2 VA
<b>insulation voltage</b>	
• rated value	690 V
• with degree of pollution 3 at AC rated value	690 V
<b>degree of pollution</b>	3
protection class IP on the front according to IEC 60529	IP20
break time maximum	20 ms
<b>reference code according to DIN 40719 extended according to IEC 204-2 according to IEC 750</b>	F
<b>reference code according to EN 61346-2</b>	F
<b>Substance Prohibitance (day/month/year)</b>	05/01/2012
<b>Net Weight</b>	138 g
<b>type of voltage of the control supply voltage</b>	AC
<b>control supply voltage 1 at AC</b>	
• at 50 Hz rated value	400 V
<b>control supply voltage frequency 1</b>	50 ... 60 Hz
number of NC contacts for auxiliary contacts instantaneous contact	0
number of NO contacts for auxiliary contacts	
• instantaneous contact	0
• leading contact	2
number of CO contacts of auxiliary contacts instantaneous contact	0
<b>Ambient conditions</b>	
<b>ambient temperature</b>	
• during operation	-20 ... +60 °C
• during storage	-50 ... +80 °C
<b>Electrical Safety</b>	
<b>protection class IP on the front according to IEC 60529</b>	IP20

touch protection on the front according to IEC 60529	finger-safe, for vertical contact from the front
<b>Short-circuit protection</b>	
design of short-circuit protection	fuse
<b>Installation/ mounting/ dimensions</b>	
fastening method	snap-on mounting
height	90 mm
width	19 mm
depth	68 mm
<b>Connections/ Terminals</b>	
type of electrical connection for auxiliary and control circuit	spring-loaded terminals

**Approvals Certificates**

Environment	General Product Approval	Test Certificates
-------------	--------------------------	-------------------

[Environmental Confirmations](#)



[Type Test Certificates/Test Report](#)

Test Certificates	Maritime application
-------------------	----------------------

[Special Test Certificate](#)



Maritime application	other
----------------------	-------



[Confirmation](#)

[Miscellaneous](#)

[Confirmation](#)

[Miscellaneous](#)



**Railway**

[Special Test Certificate](#)

**Further information**

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RV2922-2CV0>

Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RV2922-2CV0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RV2922-2CV0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[https://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RV2922-2CV0&lang=en](https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RV2922-2CV0&lang=en)



