

accessories circuit breaker 3WL 1st trip signalling switch 1 CO; S24

Model	
product brand name	SENTRON
product designation	1st trip alarm switch
design of the product	Accessories
General technical data	
degree of pollution	3
Voltage	
surge voltage resistance rated value	4 kV
Supply voltage	
operating voltage	
<ul style="list-style-type: none"> at AC at 50 Hz rated value maximum at DC rated value maximum 	250 V 250 V
Short circuit	
design of the DIAZED fuse link gG for short-circuit protection maximum permissible	6 A Dz (quick)
Mechanical Design	
Net Weight	0.018 kg
Approvals Certificates	
Environment	General Product Approval

[Environmental Con-
firmations](#)

[Environmental Con-
firmations](#)



[Confirmation](#)



Test Certificates

other

[Miscellaneous](#)

[Confirmation](#)



Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3WL9111-0AH14-0AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3WL9111-0AH14-0AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WL9111-0AH14-0AA0

CAx-Online-Generator

<https://www.siemens.com/cax>

Tender specifications

<https://www.siemens.com/specifications>

Characteristic curves

[https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP="HAUPT"></mmp_prod_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)

last modified:

6/1/2025 