

G fuse link DIN 41660 quick-response High breaking capacity Rated continuous current 6.3 A



Model		
product brand name	SETRON	
product designation	G fuse link	
design of the product	quick-response (F)	
type of miniature fuse	ceramic fuse	
General technical data		
size of the fuse link	5 x 20 mm	
melting characteristics	quick acting (F)	
type of voltage of the operating voltage	AC	
operating voltage rated value	250 V	
Main circuit		
operational current rated value	6.3 A	
Display and operation		
product component visual defect indication	No	
Mechanical Design		
Net Weight	1 g	
Approvals Certificates		
Environment	General Product Approval	other

[Environmental Con-  
firmations](#)

[Environmental Con-  
firmations](#)



[Confirmation](#)



other

[Confirmation](#)

### Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WA1822-7EF25>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/8WA1822-7EF25>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=8WA1822-7EF25](https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WA1822-7EF25)

**CAX-Online-Generator**

<https://www.siemens.com/cax>

**Tender specifications**

<https://www.siemens.com/specifications>

**Characteristic curves**

[https://curves.simaris.siemens.com/curves/<mmp\\_prod\\_noCOMP="HAUPT"></mmp\\_prod\\_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)

---

last modified:

5/26/2025 

