

Terminal, screw terminal, PE/PEN terminal, 10 mm<sup>2</sup>, green-yellow

Model	
product brand name	SETRON
product designation	Terminal blocks
design of the product	PE through-type terminal
General technical data	
insulation material	PA
terminal contact spacing	10.2 mm
Protection class	
combustibility class according to UL 94	V0
Appearance	
color	green-yellow
Product details	
product feature PEN function	No
product component required end cover plate	Yes
Number	
number of terminal levels	1
number of terminal points per terminal level	2
Connections	
stripped length	10 mm
connectable conductor cross-section solid	
• minimum	0.5 mm <sup>2</sup>
• maximum	16 mm <sup>2</sup>
connectable conductor cross-section stranded	
• minimum	16 mm <sup>2</sup>
• maximum	0.5 mm <sup>2</sup>
connectable conductor cross-section finely stranded	
• with core end processing minimum	0.5 mm <sup>2</sup>
• with core end processing maximum	10 mm <sup>2</sup>
• without core end processing minimum	0.5 mm <sup>2</sup>
• without core end processing maximum	16 mm <sup>2</sup>
tightening torque with screw-type terminals	
• minimum	1.6 N·m
• maximum	2 N·m
type of connection 1	screw-type terminal
type of connection 2	screw-type terminal
position of the terminal	lateral
Mechanical Design	
height	48 mm
height with lowest-profile installation	47.5 mm
depth	46.85 mm
length	48 mm
fastening method	TH35 DIN rail
Net Weight	29 g
material of the insulating body	PA
Environmental conditions	
ambient temperature during operation	
• minimum	-60 °C
• maximum	105 °C
Approvals Certificates	

**Environment****General Product Approval**[Environmental Con-  
firmations](#)[Environmental Con-  
firmations](#)[Confirmation](#)**General Product Ap-  
proval**

other



EG-Konf.

[Confirmation](#)[Miscellaneous](#)**Further information****Information on the packaging**<https://support.industry.siemens.com/cs/ww/en/view/109813875>**Information for data generation and storage**<https://support.industry.siemens.com/cs/ww/en/view/109995012>**Information- and Downloadcenter (Catalogs, Brochures,...)**<https://www.siemens.com/lowvoltage/catalogs>**Industry Mall (Online ordering system)**<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WH1000-0CJ07>**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**<https://support.industry.siemens.com/cs/ww/en/ps/8WH1000-0CJ07>**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**[https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=8WH1000-0CJ07](https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WH1000-0CJ07)**CAX-Online-Generator**<https://www.siemens.com/cax>**Tender specifications**<https://www.siemens.com/specifications>**Characteristic curves**[https://curves.simaris.siemens.com/curves/<mmp\\_prod\\_noCOMP="HAUPT"></mmp\\_prod\\_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)

last modified:

5/9/2025