

Terminal, spring-loaded terminal, three-tier, PE/L/L, 2.5 mm<sup>2</sup>, gray

Model	
product brand name	SENTRON
product designation	Terminal blocks
design of the product	three-tier terminal
design of terminal terminal levels internally linked	No
General technical data	
terminal contact spacing	5.2 mm
operating voltage rated value	500 V
Protection class	
combustibility class according to UL 94	V0
Main circuit	
operational current rated value	22 A
Appearance	
color	grey
Product details	
product component required end cover plate	Yes
Number	
number of terminal levels	3
number of terminal points per terminal level	2
Connections	
connectable conductor cross-section solid	
• minimum	0.08 mm <sup>2</sup>
• maximum	4 mm <sup>2</sup>
connectable conductor cross-section finely stranded	
• with core end processing minimum	0.14 mm <sup>2</sup>
• with core end processing maximum	2.5 mm <sup>2</sup>
• without core end processing minimum	0.08 mm <sup>2</sup>
• without core end processing maximum	2.5 mm <sup>2</sup>
type of connection 1	spring-loaded terminal
type of connection 2	spring-loaded terminal
position of the terminal	top
Mechanical Design	
height	99.48 mm
height with lowest-profile installation	58 mm
depth	56.5 mm
length	99.5 mm
fastening method	TH35 DIN rail
Net Weight	20 g
material of the insulating body	Other
Environmental conditions	
ambient temperature during operation	
• minimum	-60 °C
• maximum	105 °C
Approvals Certificates	
Environment	General Product Approval

[Environmental Con-  
firmations](#)

[Environmental Con-  
firmations](#)



[Confirmation](#)



[Miscellaneous](#)



[Confirmation](#)

#### Further information

**Information on the packaging**

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

**Information for data generation and storage**

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<https://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WH2030-4HF00>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/8WH2030-4HF00>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=8WH2030-4HF00](https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WH2030-4HF00)

**CAX-Online-Generator**

<https://www.siemens.com/cax>

**Tender specifications**

<https://www.siemens.com/specifications>

**Characteristic curves**

[https://curves.simaris.siemens.com/curves/<mmp\\_prod\\_noCOMP="HAUPT"></mmp\\_prod\\_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)

last modified:

5/26/2025 