

product type designation

product description

Fiber optic standard cable

Flexible glass fiber-optic cable, preferred length, preassembled

fiber optic cable (62.5/125), standard cable, splittable, pre-assembled with 4 BFOC connectors, length 50 m.



product brand name	SIMATIC NET
Technical Product Detail Page	https://l.siemens.com/1P6XV1820-5BN50
suitability for use	Cable for installation indoors and outdoors
version of the assembled FO cable	Assembled with four BFOC connectors
cable designation	AT-V(ZN)YY 2X1 G 62,5/125 OM1
wire length	50 m

optical data

attenuation factor per length	
<ul style="list-style-type: none"> at 850 nm / maximum at 1300 nm / maximum 	<p>3 dB/km</p> <p>0.8 dB/km</p>
bandwidth length product	
<ul style="list-style-type: none"> at 850 nm at 1300 nm 	<p>300 GHz·m</p> <p>800 GHz·m</p>

mechanical data

number of fibers / per FOC core	1
number of FO cores / per FOC cable	2
version of the FO conductor fiber	Multimode graded-index fiber 62.5/125 µm, OM 1
design of the FOC core	Compact core, diameter 900 µm
design of the fiber-optic cable	Segmentable outer conductor
outer diameter	
<ul style="list-style-type: none"> of the optical fibers of the optical fiber sheath of the FOC core sheath 	<p>62.5 µm</p> <p>125 µm</p> <p>3.5 mm</p>
width / of cable sheath	9.8 mm
thickness / of cable sheath	6.3 mm
material	
<ul style="list-style-type: none"> of the fiber-optic cable core of the optical fiber sheath of the FOC core sheath of the fiber-optic cable sheath of the strain relief 	<p>Quartz glass</p> <p>Quartz glass</p> <p>PVC</p> <p>PVC</p> <p>Aramid fibers and glass roving</p>
color	
<ul style="list-style-type: none"> of the FOC core sheath of cable sheath 	<p>gray</p> <p>Black</p>
bending radius	
<ul style="list-style-type: none"> with single bend / minimum permissible with multiple bends / minimum permissible 	<p>80 mm</p> <p>80 mm</p>

tensile load	
• during installation / short-term	1500 N
• during operation / maximum	1500 N
continuous shear force per length	150 N/cm
weight per length	70 kg/km
ambient conditions	
ambient temperature	
• during operation	-40 ... +85 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
• during installation	-5 ... +50 °C
fire behavior	flame-resistant acc. to IEC 60332-1-2 and IEC 60332-3-22 (Cat. A)
chemical resistance	
• to mineral oil	not resistant
• to grease	not resistant
radiological resistance / to UV radiation	resistant
protection class IP	IP20
product features, product functions, product components / general	
product feature	
• halogen-free	No
• silicon-free	Yes
product component / rodent protection	No
wire length	
• for glass FOC / for 100BaseFX / for Industrial Ethernet / maximum	4000 m
• for glass FOC / for 1000BaseSX / for Industrial Ethernet / maximum	500 m
• for glass FOC / for 1000BaseLX / for Industrial Ethernet / maximum	1000 m
• for glass FOC / with PROFIBUS / maximum	3000 m
standards, specifications, approvals	
certificate of suitability	
• RoHS conformity	Yes
further information / internet links	
internet link	
• to website: Selection guide for cables and connectors	https://support.industry.siemens.com/cs/ww/en/view/109766358
• to web page: selection aid TIA Selection Tool	https://www.siemens.com/tstcloud
• to website: Industrial communication	https://www.siemens.com/simatic-net
• to web page: SiePortal	https://sieportal.siemens.com/
• to website: Image database	https://www.automation.siemens.com/bilddb
• to website: CAX-Download-Manager	https://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com
security information / header	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry . Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert . (V4.7)
Approvals / Certificates	
General Product Approval	



[Declaration of Con-
formity](#)



[Manufacturer Declara-
tion](#)

[China RoHS](#)

General Product Approval

Maritime application

other

Industrial Communication



[Confirmation](#)



last modified:

3/10/2026