

product type designation

product description

Flexible fiber optic trailing cable

Flexible glass fiber-optic cable, preferred length, preassembled

Flex. Fiber Optic Cable (62.5/125), Trailing cable, splittable, Pre-assembled with 4 BFOC connectors, length 30 m.



product brand name

SIMATIC NET

Technical Product Detail Page

<https://i.siemens.com/1P6XV1820-6BN30>

suitability for use

Flexible cable for installation in cable carriers indoors and outdoors

version of the assembled FO cable

Assembled with four BFOC connectors

cable designation

AT-W11Y(ZN)11Y 2 G 62,5/125 OM1

wire length

30 m

optical data

attenuation factor per length

- at 850 nm / maximum
- at 1300 nm / maximum

3 dB/km

0.8 dB/km

bandwidth length product

- at 850 nm
- at 1300 nm

300 GHz·m

800 GHz·m

mechanical data

number of fibers / per FOC core

1

number of FO cores / per FOC cable

2

version of the FO conductor fiber

Multimode graded-index fiber 62.5/125 µm, OM 1

design of the FOC core

Hollow core, filled, diameter 1400 µm

design of the fiber-optic cable

Segmentable outer conductor

outer diameter

- of the optical fibers
- of the optical fiber sheath
- of the FOC core sheath

62.5 µm

125 µm

3.5 mm

outer diameter / of the cable

12.9 mm

material

- of the fiber-optic cable core
- of the optical fiber sheath
- of the FOC core sheath
- of the fiber-optic cable sheath
- of the strain relief

Quartz glass

Quartz glass

PUR

PUR

Aramid fibers, also GRP central element

color

- of the FOC core sheath
- of cable sheath

black

Black

bending radius

- with single bend / minimum permissible
- with multiple bends / minimum permissible

150 mm

150 mm

number of bending cycles

100000

tensile load	
<ul style="list-style-type: none"> during installation / short-term during operation / maximum 	<p>2000 N</p> <p>1000 N</p>
weight per length	130 kg/km
ambient conditions	
ambient temperature	
<ul style="list-style-type: none"> during operation during storage during transport during installation 	<p>-30 ... +60 °C</p> <p>-30 ... +70 °C</p> <p>-30 ... +70 °C</p> <p>-30 ... +60 °C</p>
fire behavior	flammable
chemical resistance	
<ul style="list-style-type: none"> to mineral oil to grease 	<p>acc. to IEC 60811-404 with test oil IRM 902 (acc. to ISO 1817), +100 °C, 168 h, pull speed 250 mm/min</p> <p>resistant</p>
radiological resistance / to UV radiation	resistant
protection class IP	IP20
product features, product functions, product components / general	
product feature	
<ul style="list-style-type: none"> halogen-free silicon-free 	<p>Yes</p> <p>Yes</p>
product component / rodent protection	No
wire length	
<ul style="list-style-type: none"> for glass FOC / for 100BaseFX / for Industrial Ethernet / maximum for glass FOC / for 1000BaseSX / for Industrial Ethernet / maximum for glass FOC / for 1000BaseLX / for Industrial Ethernet / maximum for glass FOC / with PROFIBUS / maximum 	<p>4000 m</p> <p>500 m</p> <p>1000 m</p> <p>3000 m</p>
standards, specifications, approvals	
certificate of suitability	
<ul style="list-style-type: none"> RoHS conformity 	Yes
further information / internet links	
internet link	
<ul style="list-style-type: none"> to website: Selection guide for cables and connectors to web page: selection aid TIA Selection Tool to website: Industrial communication to web page: SiePortal to website: Image database to website: CAx-Download-Manager to website: Industry Online Support 	<p>https://support.industry.siemens.com/cs/ww/en/view/109766358</p> <p>https://www.siemens.com/tstcloud</p> <p>https://www.siemens.com/simatic-net</p> <p>https://sieportal.siemens.com/</p> <p>https://www.automation.siemens.com/bilddb</p> <p>https://www.siemens.com/cax</p> <p>https://support.industry.siemens.com</p>
security information / header	
security information	<p>Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)</p>
Approvals / Certificates	
General Product Approval	



EG-Konf.

[Declaration of Con-
formity](#)



CCC

[Manufacturer Declara-
tion](#)

[China RoHS](#)

General Product Ap-
proval

Maritime application



RCM



DNV

last modified:

3/10/2026