

product type designation

product description

Indoor fiber optic indoor cable

Glass fiber-optic cable, preferred length, preassembled

Indoor Fiber Optic (62.5/125), halogen-free, non-crush and flame-retardant fiber-optic internal cable pre-assembled with 4 BFOC connectors, length 75 m.



product brand name

SIMATIC NET

Technical Product Detail Page

<https://l.siemens.com/1P6XV1820-7BN75>

suitability for use

Non-crush, halogen-free and flame-retardant cable for indoor installation

version of the assembled FO cable

Assembled with four BFOC connectors

cable designation

I-V(ZN)HH 2x1 G 62,5/125 OM1

wire length

75 m

optical data

attenuation factor per length

- at 850 nm / maximum
- at 1300 nm / maximum

3 dB/km

0.8 dB/km

bandwidth length product

- at 850 nm
- at 1300 nm

300 GHz·m

800 GHz·m

mechanical data

number of fibers / per FOC core

1

number of FO cores / per FOC cable

2

version of the FO conductor fiber

Multimode graded-index fiber 62.5/125 µm, OM 1

design of the FOC core

Solid core, diameter 900 µm

design of the fiber-optic cable

Segmentable inner conductor

outer diameter

- of the optical fibers
- of the optical fiber sheath
- of the FOC core sheath

62.5 µm

125 µm

2.9 mm

symmetrical deviation / of the outer diameter of the FOC core sheath

0.1 mm

width / of cable sheath

6.8 mm

thickness / of cable sheath

3.9 mm

material

- of the fiber-optic cable core
- of the optical fiber sheath
- of the FOC core sheath
- of the fiber-optic cable sheath
- of the strain relief

Quartz glass

Quartz glass

FRNC

FRNC

Aramid fibers

color

- of the FOC core sheath
- of cable sheath

gray

orange

bending radius

<ul style="list-style-type: none"> • with single bend / minimum permissible 	30 mm
<ul style="list-style-type: none"> • with multiple bends / minimum permissible 	50 mm
tensile load	
<ul style="list-style-type: none"> • during installation / short-term 	800 N
<ul style="list-style-type: none"> • during operation / maximum 	200 N
short-term shear force per length	300 N/cm
continuous shear force per length	100 N/cm
weight per length	30 kg/km
ambient conditions	
ambient temperature	
<ul style="list-style-type: none"> • during operation 	-20 ... +60 °C
<ul style="list-style-type: none"> • during storage 	-25 ... +70 °C
<ul style="list-style-type: none"> • during transport 	-25 ... +70 °C
<ul style="list-style-type: none"> • during installation 	-5 ... +50 °C
fire behavior	flame-resistant acc. to IEC 60332-1-2 and IEC 60332-3-22 (Cat. A)
chemical resistance	
<ul style="list-style-type: none"> • to mineral oil 	acc. to IEC 60811-404 with test oil IRM 902 (acc. to ISO 1817), +70 °C, 4 h and +25 °C, 168 h
<ul style="list-style-type: none"> • to grease 	not resistant
radiological resistance / to UV radiation	not resistant
protection class IP	IP20
product features, product functions, product components / general	
product feature	
<ul style="list-style-type: none"> • halogen-free 	Yes
<ul style="list-style-type: none"> • silicon-free 	Yes
product component / rodent protection	No
wire length	
<ul style="list-style-type: none"> • for glass FOC / for 100BaseFX / for Industrial Ethernet / maximum 	4000 m
<ul style="list-style-type: none"> • for glass FOC / for 1000BaseSX / for Industrial Ethernet / maximum 	500 m
<ul style="list-style-type: none"> • for glass FOC / for 1000BaseLX / for Industrial Ethernet / maximum 	1000 m
<ul style="list-style-type: none"> • for glass FOC / with PROFIBUS / maximum 	3000 m
standards, specifications, approvals	
certificate of suitability	
<ul style="list-style-type: none"> • RoHS conformity 	Yes
further information / internet links	
internet link	
<ul style="list-style-type: none"> • to website: Selection guide for cables and connectors 	https://support.industry.siemens.com/cs/ww/en/view/109766358
<ul style="list-style-type: none"> • to web page: selection aid TIA Selection Tool 	https://www.siemens.com/tstcloud
<ul style="list-style-type: none"> • to website: Industrial communication 	https://www.siemens.com/simatic-net
<ul style="list-style-type: none"> • to web page: SiePortal 	https://sieportal.siemens.com/
<ul style="list-style-type: none"> • to website: Image database 	https://www.automation.siemens.com/bilddb
<ul style="list-style-type: none"> • to website: CAx-Download-Manager 	https://www.siemens.com/cax
<ul style="list-style-type: none"> • to website: Industry Online Support 	https://support.industry.siemens.com
security information / header	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry . Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates,

Approvals / Certificates

General Product Approval



[Declaration of Conformity](#)



[Manufacturer Declaration](#)

[China RoHS](#)

General Product Approval

Maritime application

Industrial Communication



last modified:

3/10/2026