


### product type designation

product description



### FO Ground Cable

Glass fiber-optic cable, preferred length, preassembled

FO Ground Cable 50/125, pre-assembled 2x2 BFOC connectors, insertion aid, length 300 m.

product brand name	SIMATIC NET
Technical Product Detail Page	<a href="https://l.siemens.com/1P6XV1873-3GT30">https://l.siemens.com/1P6XV1873-3GT30</a>
suitability for use	Waterproof cable (lengthwise and sideways) with non-metallic protection against rodents for use outdoors as well as for direct routing underground
version of the assembled FO cable	Assembled with four BFOC connectors
cable designation	AT-WQ(ZN)Y(ZN)B2Y 2G 50/125 OM2++
wire length	300 m
<b>optical data</b>	
attenuation factor per length	
• at 850 nm / maximum	2.7 dB/km
• at 1300 nm / maximum	0.7 dB/km
bandwidth length product	
• at 850 nm	600 GHz·m
• at 1300 nm	1200 GHz·m
<b>mechanical data</b>	
number of fibers / per FOC core	1
number of FO cores / per FOC cable	2
version of the FO conductor fiber	Multi-mode gradient fiber 50/125 µm, OM 2
design of the FOC core	Hollow core, filled, diameter 1400 µm
design of the fiber-optic cable	segmentable
outer diameter	
• of the optical fibers	50 µm
• of the optical fiber sheath	125 µm
• of the FOC core sheath	2.9 mm
symmetrical deviation / of the outer diameter of the FOC core sheath	0.1 mm
outer diameter / of the cable	10.5 mm
symmetrical deviation / of the outer diameter of the line	0.5 mm
material	
• of the fiber-optic cable core	Quartz glass
• of the optical fiber sheath	Quartz glass
• of the FOC core sheath	PVC
• of the fiber-optic cable sheath	PE
• of the strain relief	Aramid fibers
color	
• of the FOC core sheath	orange/black
• of cable sheath	Black
bending radius	

<ul style="list-style-type: none"> <li>• with single bend / minimum permissible</li> </ul>	105 mm
<ul style="list-style-type: none"> <li>• with multiple bends / minimum permissible</li> </ul>	155 mm
tensile load	
<ul style="list-style-type: none"> <li>• during installation / short-term</li> </ul>	2000 N
<ul style="list-style-type: none"> <li>• during operation / maximum</li> </ul>	800 N
short-term shear force per length	500 N/cm
continuous shear force per length	300 N/cm
weight per length	90 kg/km
<b>ambient conditions</b>	
ambient temperature	
<ul style="list-style-type: none"> <li>• during operation</li> </ul>	-40 ... +75 °C
<ul style="list-style-type: none"> <li>• during storage</li> </ul>	-40 ... +75 °C
<ul style="list-style-type: none"> <li>• during transport</li> </ul>	-40 ... +75 °C
<ul style="list-style-type: none"> <li>• during installation</li> </ul>	-5 ... +50 °C
fire behavior	flammable
chemical resistance	
<ul style="list-style-type: none"> <li>• to mineral oil</li> </ul>	resistant
<ul style="list-style-type: none"> <li>• to grease</li> </ul>	resistant
<ul style="list-style-type: none"> <li>• to water</li> </ul>	resistant
radiological resistance / to UV radiation	resistant
protection class IP	IP20
<b>product features, product functions, product components / general</b>	
product feature	
<ul style="list-style-type: none"> <li>• halogen-free</li> </ul>	No
<ul style="list-style-type: none"> <li>• silicon-free</li> </ul>	Yes
product component / rodent protection	Yes
wire length	
<ul style="list-style-type: none"> <li>• for glass FOC / for 100BaseFX / for Industrial Ethernet / maximum</li> </ul>	5000 m
<ul style="list-style-type: none"> <li>• for glass FOC / for 1000BaseSX / for Industrial Ethernet / maximum</li> </ul>	750 m
<ul style="list-style-type: none"> <li>• for glass FOC / for 1000BaseLX / for Industrial Ethernet / maximum</li> </ul>	2000 m
<ul style="list-style-type: none"> <li>• for glass FOC / with PROFIBUS / maximum</li> </ul>	3000 m
<b>standards, specifications, approvals</b>	
certificate of suitability	
<ul style="list-style-type: none"> <li>• RoHS conformity</li> </ul>	Yes
<b>further information / internet links</b>	
internet link	
<ul style="list-style-type: none"> <li>• to website: Selection guide for cables and connectors</li> </ul>	<a href="https://support.industry.siemens.com/cs/ww/en/view/109766358">https://support.industry.siemens.com/cs/ww/en/view/109766358</a>
<ul style="list-style-type: none"> <li>• to web page: selection aid TIA Selection Tool</li> </ul>	<a href="https://www.siemens.com/tstcloud">https://www.siemens.com/tstcloud</a>
<ul style="list-style-type: none"> <li>• to website: Industrial communication</li> </ul>	<a href="https://www.siemens.com/simatic-net">https://www.siemens.com/simatic-net</a>
<ul style="list-style-type: none"> <li>• to web page: SiePortal</li> </ul>	<a href="https://sieportal.siemens.com/">https://sieportal.siemens.com/</a>
<ul style="list-style-type: none"> <li>• to website: Image database</li> </ul>	<a href="https://www.automation.siemens.com/bilddb">https://www.automation.siemens.com/bilddb</a>
<ul style="list-style-type: none"> <li>• to website: CAx-Download-Manager</li> </ul>	<a href="https://www.siemens.com/cax">https://www.siemens.com/cax</a>
<ul style="list-style-type: none"> <li>• to website: Industry Online Support</li> </ul>	<a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>
<b>security information / header</b>	
security information	<p>Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit <a href="http://www.siemens.com/cybersecurity-industry">www.siemens.com/cybersecurity-industry</a>. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase</p>

customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under [https://www.siemens.com/cert. \(V4.7\)](https://www.siemens.com/cert. (V4.7))

Approvals / Certificates

General Product Approval



[Manufacturer Declaration](#)

[China RoHS](#)



other

Industrial Communication

[Confirmation](#)



last modified:

3/10/2026