



Figure similar

power supply; phases: 1; Pn(kW): 0.144; Upri(V): 400-230+/-15; Usec(V DC): 24; Isec(A DC): 6; F(Hz): 50...60; vector group/shielding winding: II0 /0; protection class: I; temperature rise/insulation class: 40 /B; W(%): 5; IP00; connection: screw connection; mounting: screws / DIN rail; EN 61558, EN 61131-2 >safety transformer<

General technical data		
product designation		<a href="#">4AV4106-2EB00-0A</a>
product brand name		SIDAC
vector group		II0
certificate of suitability		CE
product function		
• temperature monitoring		No
• insulation monitoring		No
• short-circuit and overload proof		No
• varistor protective wiring		Yes
operating resource protection class		I
number of shielding windings		0
Inputs		
phase number of the inputs		1
type of current of the inputs		AC
input voltage		
• _1 rated value	V	415
• _2 rated value	V	400
• _3 rated value	V	385
• _4 rated value	V	245
• _5 rated value	V	230
• _6 rated value	V	215
electrical input frequency		
• minimum	Hz	50
• maximum	Hz	60
input voltage		
• minimum	V	193.5
• maximum	V	439.89
input current		
• _1 rated value	A	0.56
• _2 rated value	A	0.58
• _3 rated value	A	0.6
• _4 rated value	A	0.94
• _5 rated value	A	1
type of electrical connection at input for main current circuit		screw-type terminals
Outputs		
type of current		

• _1 at output		DC
<b>output voltage</b>		
• _1 rated value	V	24
<b>output voltage of the measurement signal at analog output at DC maximum</b>	V	30
<b>output voltage of the measurement signal at analog output at DC minimum</b>	V	20.4
<b>output current</b>		
• _1 rated value	A	6
<b>type of electrical connection at output for main current circuit</b>		screw-type terminals
<b>relative residual ripple</b>		
• of the output voltage 1 for main current circuit maximum	%	5

#### Ambient conditions

<b>thermal class according to IEC 60085</b>		B
<b>ambient temperature rated value</b>	°C	40
<b>protection class IP</b>		IP00

#### Mechanical data

<b>fastening method</b>		screws / DIN rail
<b>construction form of the iron core</b>		EI 96/58
<b>width</b>	mm	96
<b>height</b>	mm	152
<b>depth</b>	mm	108

#### Certificates/ approvals

General Product Approval	other	Environment
--------------------------	-------	-------------



EG-Konf.



[Confirmation](#)

[Confirmation](#)



[Environmental Confirmations](#)

#### Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=4AV4106-2EB00-0A>

Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=4AV4106-2EB00-0A>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/4AV4106-2EB00-0A>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[https://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=4AV4106-2EB00-0A&lang=en](https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=4AV4106-2EB00-0A&lang=en)

last modified:

5/9/2026