

# INTERCONNECTION

## Pluggable Terminal Strips Plug in Style

- Moulded in white UL94-V2 self extinguishing PA6
- Easily cut to size
- IMQ, CE Approved
- UL94-VO (160°C) flame retardant version available on request.
- Available pre-cut to length

CTSN/MF



### SPECIFICATION



|                     |                                          |
|---------------------|------------------------------------------|
| Voltage (max)       | 450V AC                                  |
| Working temperature | 85°C                                     |
| Short period        | 85°C                                     |
| No. of poles        | 12                                       |
| Moulding            | UL94-V2 Self extinguishing PA 6          |
| Conducting bush     | Brass                                    |
| Screws              | Zinc, colour passivated and tropicalised |

| TYPE NO.     | SIZE / RATING | INSERT DIAMETER | TERMINAL SCREWS | LENGTH  | WIDTH  | HEIGHT | PITCH | FIXING HOLE DIAMETER | MAX CURRENT |
|--------------|---------------|-----------------|-----------------|---------|--------|--------|-------|----------------------|-------------|
| CTSN431/12MF | 8mm/6A        | 2.9mm           | M3              | 94.8mm  | 16mm   | 15.3mm | 8mm   | 2.5mm                | 17.5A       |
| CTSN433/12MF | 10mm/10A      | 3.4mm           | M3              | 119mm   | 20.3mm | 16.4mm | 10mm  | 3.2mm                | 24A         |
| CTSN434/12MF | 12mm/16A      | 4.3mm           | M3.5            | 141.9mm | 23.2mm | 19.2mm | 12mm  | 3.3mm                | 57A         |

## Strain relief

- Clamps external conductors in lighting fixtures according to EN 60598
- Natural colour PA6
- Takes the strain on the wires
- Prevents conductors from twisting
- Protects wire coating from abrasion and friction

CSR



| TYPE NO. | TERMINAL STRIP     | LENGTH | WIDTH | HEIGHT |
|----------|--------------------|--------|-------|--------|
| CSR1     | CTSN431            | 49.5mm | 31mm  | 22.5mm |
| CSR2     | CTSN433 / CTSN433T | 52.5mm | 31mm  | 22.5mm |
| CSR3     | CTSN434            | 54.5mm | 31mm  | 22.5mm |

