

MYMGC3R32EFPF2RB


In Production

Recommended

RoHS



Appearance & Shape



Features

- Input voltage ranges from 4.3 to 5.5V
- Fixed 4 outputs voltage, 1.2V, 1.8V, 3.3V and 2.5V
- Quick transient response to load change
- Small package, 11.9×15×2.4mm
- Over current protection
- Thermal Protection
- Enable control
- Power Good signal
- I2C function
- High Reliability / Heat Shock Testing, 700cycle (-40 to +125degC)

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

MYMGC3R32EFPF2RB

Specifications

Iout(A)Max	2.5A
Vin(V)	4.3V to 5.5V
Vin(V)typ	5V
Vout(V)	1.2V
Vout(V)typ	1.2V
LineRegulation (%)	-1% to 1%
LoadRegulation (%)	-1% to 1%
Outputs (#)	4
Efficiency (%)	88%
Switching frequency (kHz)	1650kHz
Size(mm)W	11.9mm
Size(mm)L	15.0mm
Size(mm)T	2.4mm
Operatingtemperature(degC)	-40°C to 85°C
Circuit topology	Buck(Step-down)
Package	SMD
Type	Modules (integrated components)
Productseries	MYMGC
Product Series Features	MYMGC series which is POL (Point of Load) is multiple output MonoBK with I2C interface
Iout2(A)Max	1A
Vout2 (V)	1.8V
Vout2 (V)typ	1.8V

LineRegulation2 (%)	-1% to 1%
LoadRegulation2 (%)	-1% to 1%
Iout3(A)Max	2A
Vout3 (V)	3.3V
Vout3 (V)typ	3.3V
LineRegulation3 (%)	-1% to 1%
LoadRegulation3 (%)	-1% to 1%
Iout4(A)Max	1.5A
Vout4 (V)	2.5V
Vout4 (V)typ	2.5V
LineRegulation4 (%)	-1% to 1%
LoadRegulation4 (%)	-1% to 1%
Brand	Murata

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.