



RADIAL-LEADED DEVICES



✓ Active

TE CONNECTIVITY (TE)

RKEF375

[Raychem](#) | [PolySwitch Devices](#) , [PPTC](#) , [RKEF](#)

RKEF375

TE Internal Number: RF3375-000

[Always EU RoHS/ELV Compliant](#)

Hold Current (Room Temperature) (A) **3.75**

Voltage (Max) (V) **60**

Current (Max) (A) **40**

Lead Type **Straight**

Trip Current (Room Temperature) (A) **7.5**

Catalog Pages/Data Sheets

CATALOG PAGES FOR POLYSWITCH RADIAL

PDF
English

Product Specifications

Product Specification

RKEF375

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information.

Product Type Features

Product Type

PolySwitch Resettable Devices

Electrical Characteristics

Hold Current (Room Temperature) (A)

3.75

Voltage (Max) (V)

60

Current (Max) (A)

40

Trip Current (Room Temperature) (A)

7.5

Resistance (Min) (Ω)

.017

Resistance (Max) (Ω)

.04

Resistance (Max) (20°C, 1-Hr Post Trip) (Ω)

.06

Time to Trip (Max) (seconds)

22

Power Dissipation (Typical) (W)

3.4

Body Features

Lead Type

Straight

Lead Spacing (mm)

10.15



	Lead spacing (mm)	10.15
	Coating	Coated
Termination Features	Construction	Radial-Leaded
Usage Conditions	Operating Temperature (Max) (°C)	85
Industry Standards	CSA File Number	CA78165
	TUV Certificate Number	Available on Request (per IEC 60730-1)
	UL File Number	E74889
Packaging Features	Packaging Method	Bag
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	

CUSTOMERS ALSO BOUGHT

RADIAL-LEADED DEVICES



RXEF375
RXEF375

 Save to List

 Find Similar Products

RECTANGULAR POWER CONNECTORS



06P MICRO MNL ASSY,
VRT, THRU, LF
3-794681-6

 Save to List

 Find Similar Products

RECTANGULAR POWER CONNECTORS




02P MICRO MNL ASSY,
VRT, THRU, LF
3-794682-2

 Save to List

 Find Similar Products

WIRE-TO-BOARD HEADERS & RECEPTACLES



14 MTE HDR SRST LATCH
.100CL
6-103735-3

 Save to List

 Find Similar Products