



CIRCUIT PROTECTION

RADIAL-LEADED DEVICES



✓ Active

TE CONNECTIVITY (TE)

RKEF135

Raychem | PolySwitch Devices , PPTC , RKEF

RKEF135

TE Internal Number: RF3369-000

Always EU RoHS/ELV Compliant

Hold Current (Room Temperature) (A) **1.35**

Voltage (Max) (V) **60**

Current (Max) (A) **40**

Lead Type **Straight**

Trip Current (Room Temperature) (A) **2.7**

Catalog Pages/Data Sheets

CATALOG PAGES FOR POLYSWITCH RADIAL

PDF
English

Product Specifications

Product Specification

RKEF135

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information.

Product Type Features

Product Type

PolySwitch Resettable Devices

Electrical Characteristics

Hold Current (Room Temperature) (A)	1.35
Voltage (Max) (V)	60
Current (Max) (A)	40
Trip Current (Room Temperature) (A)	2.7
Resistance (Min) (Ω)	.11
Resistance (Max) (Ω)	.22
Resistance (Max) (20°C, 1-Hr Post Trip) (Ω)	.37
Time to Trip (Max) (seconds)	4.5
Power Dissipation (Typical) (W)	2.3



Body Features

Lead Type

Straight

Lead Spacing (mm)

5.08

Lead spacing (mm)

3.00

Coating

Coated

Termination Features

Construction

Radial-Leaded

Usage Conditions

Operating Temperature (Max) (°C)

85

Industry Standards

CSA File Number

CA78165

TUV Certificate Number

Available on Request (per IEC 60730-1)

UL File Number

E74889

Packaging Features

Packaging Method

Bag

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

RECTANGULAR POWER CONNECTORS	RECTANGULAR POWER CONNECTORS	SURFACE MOUNT DEVICES	BOARD-TO-BOARD HEADERS & RECEPTACLES
			
10P MINI UMNL R/A HDR ASSY SN 1-770971-0	08P MICRO MNL ASSY, RA, SMT, L 3-794627-8	SMD185F-2 SMD185F-2	2MM FB, ASY, 24, SIG, REC, SL, 2.73 5536507-1
Save to List Find Similar Products			