

RRC2057

Rechargeable Smart Battery Pack Li-Ion

7.20V / 6.90Ah / 49.7Wh

P/N: 100569



Features

- Worldwide approvals and certification of safety standards
- No development costs, fast time-to-market
- Smart batteries with numerous features according to the SMBus specification
- Integrated LED State of Charge (SoC) indicator
- State-of-the-art lithium-ion cells with the market's highest energy density
- High discharge performance
- JEITA charging profile optimization
- Numerous and redundant safety features, e.g.:
 - CUV (Cell Under Voltage): protection against deep discharge
 - COV (Cell Over Voltage): protection against over charge
 - OTC (Over Temperature in Charge): protection against overheating while charging
 - OTD (Over Temperature in Discharge): protection against overheating during discharging
 - Life-End-Control: protection against rapid cell ageing
- Increased ESD protection up to 8kV
- SHA-1 cryptosystem to prevent plagiarism

Applications

Suitable for use with tablet PC's, notebooks, industrial and medical devices, etc

Specification

General	
Delivery status battery capacity	30%
Compliance information	CE / UL2054 / FCC / PSE / KC / Gost / EAC / CQC / RCM / IEC62133 / UN38.3 / RoHS / REACH / BIS / TISI / BSMI
Operating temperature	0°C to 45°C (charge) -20°C to 60°C (discharge)
Storage temperature	-20°C to 50°C max. -20°C to 25°C recommended
Electrical Parameters	
Nominal voltage	7.20V
Nominal capacity	6.90Ah
Initial impedance	<180mΩ @ 1kHz at 25°C
Max. charge current	4.83A
Max. charge voltage	8.40V
Max. discharge	9.50A
Life expectancy	300 cycles with ≥ 75% of initial capacity CC/CV Charge: 3.35A / 8.40V Discharge: 6.70A down to 5.00V @25°C
Battery Dimensions	
Length	85.1mm +0.25/-0.25
Width	77.4mm +0.25/-0.25
Thickness	22.4mm +0.60/-0.40
Weight	230g
Contacts	+, D, C, T, -
Safety Parameters PCM	
Overcharge detection voltage / cell	4.23V
Overdischarge detection voltage / cell	2.50V
Overcharge detection current	6.70A
Overdischarge detection current	10.50A

Recommended Accessories

Type		Product	P/N	Application
Battery Charger		RRC-SMB-UBC RRC-SMB-UBC-M	100485 110105	65W standard battery charger for optimized charging process. With external power supply for worldwide use.
Battery Charger		RRC-SMB-MBC RRC-SMB-MBC-M	110017 110104	50W standard battery charger for optimized charging process. With external power supply for worldwide use.
Battery Charger		RRC-SMB-DBC	110111	Dual bay standard battery charger for optimized charging process. With external power supply for worldwide use.
Power Management Module		RRC-PMM240	100576	Power management module for smart battery charging with automatic power source selection. Fits to all RRC20xx standard smart batteries.
Power Supply AC/DC		PS65	210919	External power supply for power management module RRC-PMM240 or for mobile devices. Included in RRC-SMB-UBC/MBC.
3-pol AC-Cable		US-Version EU-Version UK-Version AU-Version	210950 210951 211333 211334	Country specific power cable for PS65.
Car Adapter DC/DC		RRC-SMB-CAR	110041	90W car adapter with USB charging port. Power supplying in cars and trucks for RRC-SMB-UBC, RRC-SMB-MBC, RRC-PMM240 or mobile devices.

Type	Product	P/N	Application
Design-In Tool 	SMBus-Reader	100127	Simple read out of SMBus batteries data. No external power supply required. 5way blade connector and RS232 interface.
Battery Connector 	SMBus-Battery-Cable	400665	Extension cable for battery applications. Suitable for RRC204x and RRC205x batteries.
Battery Connector 	RRC-MC20-90-10 RRC-MC20-180-10	210519 210518	Mating connector for standard smart batteries from RRC. Suitable for RRC20xx batteries. Available for 90° or 180° PCB mounting.

Germany/Headquarters

RRC power solutions GmbH
Technologiepark 1
66424 Homburg / Saar

Tel.: +49 6841 98090
Fax: +49 6841 9809280
Email: sales@rrc-ps.de
Web: www.rrc-ps.de

USA

RRC power solutions Inc.
18340 Yorba Linda Blvd.,
107-437 Yorba Linda,
CA 92886-4104

Tel.: +1 714 777 3604
Fax: +1 714 777 3658
Email: usa@rrc-ps.com
Web: www.rrc-ps.com

Hong Kong

RRC power solutions Ltd.
S-V,6/F, Valiant Industrial
Centre 2-12 Au Pui Wan Street
Fo Tan, N.T., Hong Kong

Tel.: +852 2376 0106
Fax: +852 2375 0107
Email: hkrrc@rrc-ps.cn
Web: www.rrc-ps.com

China

RRC power solutions Ltd.
Room 1306, C Building,
Tianan International building,
Renmin South Road, Luohu
District, Shenzhen 518021

Tel.: +86 755 8374 1908
Fax: +86 755 8374 1861
Email: hkrrc@rrc-ps.cn
Web: www.rrc-ps.com