

Connecting cable, 10-pole 8 mm

General technical data		
product brand name		SIRIUS
product designation		connecting cable, 10 poles
protection class IP on the front according to IEC 60529		IP20
touch protection on the front according to IEC 60529		Finger-safe, for vertical contact
relative humidity during operation	%	10 ... 90
ambient temperature		
• during transport	°C	-55 ... +80
• during storage	°C	-55 ... +80
• during operation	°C	-20 ... +60
reference code according to EN 61346-2		W

Installation/ mounting/ dimensions		
width	mm	25

Connections/ Terminals		
wire length of connection cable	mm	25

Certificates/ approvals			
certificate of suitability		IEC / EN 60947-6-2	
General Product Approval		EMV	Maritime application



other	Environment		
<a href="#">Confirmation</a>	<a href="#">Confirmation</a>		<a href="#">Environmental Confirmations</a>

### Further information

Information on the packaging  
<https://support.industry.siemens.com/cs/ww/en/view/109813875>  
 Information for data generation and storage  
<https://support.industry.siemens.com/cs/ww/en/view/109995012>  
 Information- and Downloadcenter (Catalogs, Brochures,...)  
<https://www.siemens.com/ic10>  
 Industry Mall (Online ordering system)  
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RA6932-0A>  
 Cax online generator  
<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RA6932-0A>  
 Service&Support (Manuals, Certificates, Characteristics, FAQs,...)  
<https://support.industry.siemens.com/cs/ww/en/ps/3RA6932-0A>  
 Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)  
[https://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RA6932-0A&lang=en](https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RA6932-0A&lang=en)

last modified:

4/2/2025