

AUXILIARY SWITCH 1NO+1NC FOR MCB 5SL, 5SY, 5SP, ON-OFF-SW. 5TL1, RCBO 5SU1, RCD 5SV



Model	
product brandname	SENTRON
Product designation	Auxiliary current switch
Design of the product	Mountable
Design of the product / factory mounted	No
Control current	
Type of voltage / of control voltage	AC/DC
Product details	
Product extension	Auxiliary current switch
can be mounted	RCBO and miniature circuit breaker
Number	
Number of fault signal contacts	0
Number of NC contacts	1
Number of NO contacts	1
Number of CO contacts	0
Mechanical Design	
Number of width units	0.5

Net weight	55 g			
Equipment marking	SF			
• acc. to DIN EN 81346-2				
General Product Approval		Declaration of Conformity	Test Certificates	Shipping Approval
				
CCC	UL	VDE	EG-Konf.	LRS

[sonstig](#)

other

[sonstig](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3010>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5ST3010/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)



http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3010

CAX-Online-Generator


<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



13 21



14 22

