

Terminal, iPo plug-in terminal, through-type terminal, 4 mm², gray

| Model | |
|--|--|
| product brand name | SENTRON |
| product designation | Terminal blocks |
| design of the product | iPo through-type terminal |
| product version | through-type terminal, for mounting on mounting rail acc. to IEC 60715 |
| design of terminal terminal levels internally linked | No |
| General technical data | |
| terminal contact spacing | 6 mm |
| operating voltage rated value | 800 V |
| Protection class | |
| combustibility class according to UL 94 | V0 |
| Main circuit | |
| operational current rated value | 32 A |
| Appearance | |
| color | grey |
| Product details | |
| product component required end cover plate | Yes |
| Number | |
| number of terminal levels | 1 |
| number of terminal points per terminal level | 4 |
| Connections | |
| connectable conductor cross-section solid | |
| • minimum | 0.2 mm ² |
| • maximum | 6 mm ² |
| connectable conductor cross-section stranded | |
| • minimum | 0.2 mm ² |
| • maximum | 6 mm ² |
| connectable conductor cross-section finely stranded | |
| • with core end processing minimum | 0.25 mm ² |
| • with core end processing maximum | 4 mm ² |
| • without core end processing minimum | 0.2 mm ² |
| • without core end processing maximum | 6 mm ² |
| type of connection 1 | plug terminal connection |
| type of connection 2 | plug terminal connection |
| position of the terminal | top |
| Mechanical Design | |
| height | 76.93 mm |
| height with lowest-profile installation | 36.5 mm |
| depth | 35.3 mm |
| length | 77 mm |
| fastening method | TH35 DIN rail |
| Net Weight | 13 g |
| material of the insulating body | Other |
| Environmental conditions | |
| ambient temperature during operation | |
| • minimum | -60 °C |
| • maximum | 105 °C |
| Approvals Certificates | |
| Environment | General Product Approval |

[Environmental Con-
firmations](#)



[Confirmation](#)



other

[Confirmation](#)



Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WH6004-0AG00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/8WH6004-0AG00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WH6004-0AG00

CAX-Online-Generator

<https://www.siemens.com/cax>

Tender specifications

<https://www.siemens.com/specifications>

Characteristic curves

[https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP="HAUPT"></mmp_prod_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)

last modified:

2/24/2026

