

!!! phased-out product !!! the preferred successor is 3RQ4052-2SM30 output coupler optocoupler 1 NO, transistor, 24 V DC output max. 30 V DC, 2 A short-circuit-proof spring-loaded terminal (push-in) width 6.2 mm thermal current 2 A

| | |
|---|---|
| product brand name | SIRIUS |
| product category | SIRIUS 3RQ3 coupling relays in slim design |
| product designation | Coupling relays with semiconductor output (not plug-in) |
| design of the product | Output coupling link |
| product type designation | 3RQ3 |
| General technical data | |
| display version LED | Yes |
| product feature protective coating on printed-circuit board | No |
| product component | |
| • relay output | No |
| • semi-conductor output | Yes |
| consumed active power | 0.3 W |
| insulation voltage for overvoltage category III according to IEC 60664 with degree of pollution 3 rated value | 50 V |
| surge voltage resistance rated value | 2.5 kV |
| flammability class of enclosure material | UL94 V-0 |
| shock resistance | |
| • according to IEC 60068-2-27 | sinusoidal half-wave 15 g / 11 ms |
| vibration resistance | |
| • according to IEC 60068-2-6 | 6 ... 150 Hz: 2 g |
| switching frequency | 100 Hz |
| thermal current | 2 A |
| reference code according to IEC 81346-2 | K |
| Substance Prohibitance (day/month/year) | 03/25/2015 |
| Net Weight | 0.03 kg |
| Control circuit/ Control | |
| control supply voltage at DC rated value | 11 ... 30 V |
| operating range factor control supply voltage rated value at DC | |
| • initial value | 1 |
| • full-scale value | 1 |
| minimum switching voltage when switching on | 11 V |
| maximum switching voltage when switching off | 5 V |
| ON-delay time | |
| • at DC maximum | 0.2 ms |
| OFF-delay time maximum | 0.3 ms |
| Mechanical data | |
| product component plug-in socket | No |
| Auxiliary circuit | |
| type of switching contact | NO contact |
| number of NO contacts for auxiliary contacts | 1 |
| Main circuit | |
| type of voltage | DC |
| Inputs/ Outputs | |
| property of the output short-circuit proof | Yes |
| switching voltage of the semiconductor output at DC | 10 ... 30 V |
| ampacity of the semiconductor output at DC | 5 mA ... 2 A |
| Electromagnetic compatibility | |
| EMC emitted interference according to IEC 60947-1 | ambience A (industrial sector) |

| | |
|--|---|
| EMC immunity according to IEC 60947-1 | corresponds to degree of severity 3 |
| conducted interference | |
| <ul style="list-style-type: none"> • due to burst according to IEC 61000-4-4 | 2 kV |
| <ul style="list-style-type: none"> • due to conductor-earth surge according to IEC 61000-4-5 | 2 kV |
| <ul style="list-style-type: none"> • due to conductor-conductor surge according to IEC 61000-4-5 | 1 kV |
| field-based interference according to IEC 61000-4-3 | 10 V/m |
| electrostatic discharge according to IEC 61000-4-2 | 6 kV contact discharge / 8 kV air discharge |
| Display | |
| display version as status display by LED | LED green |
| Connections/ Terminals | |
| product function removable terminal | No |
| type of electrical connection | |
| <ul style="list-style-type: none"> • for auxiliary and control circuit | spring-loaded terminals (push-in) |
| type of connectable conductor cross-sections | |
| <ul style="list-style-type: none"> • solid | 1x (0.25 ... 2.5 mm ²) |
| <ul style="list-style-type: none"> • finely stranded with core end processing | 1x (0.25 ... 1.5 mm ²) |
| <ul style="list-style-type: none"> • finely stranded without core end processing | 1x (0.25 ... 2.5 mm ²) |
| <ul style="list-style-type: none"> • for AWG cables solid | 1x (20 ... 14) |
| <ul style="list-style-type: none"> • for AWG cables stranded | 1x (20 ... 14) |
| connectable conductor cross-section | |
| <ul style="list-style-type: none"> • solid | 0.25 ... 2.5 mm ² |
| <ul style="list-style-type: none"> • finely stranded with core end processing | 0.25 ... 1.5 mm ² |
| <ul style="list-style-type: none"> • finely stranded without core end processing | 0.25 ... 2.5 mm ² |
| AWG number as coded connectable conductor cross section | |
| <ul style="list-style-type: none"> • solid | 20 ... 14 |
| <ul style="list-style-type: none"> • stranded | 20 ... 14 |
| Installation/ mounting/ dimensions | |
| mounting position | any |
| fastening method | snap-on mounting |
| height | 93 mm |
| width | 6.2 mm |
| depth | 72.5 mm |
| required spacing | |
| <ul style="list-style-type: none"> • with side-by-side mounting <ul style="list-style-type: none"> — forwards — backwards — upwards — downwards — at the side | 0 mm |
| <ul style="list-style-type: none"> • for grounded parts <ul style="list-style-type: none"> — forwards — backwards — upwards — at the side — downwards | 0 mm |
| <ul style="list-style-type: none"> • for live parts <ul style="list-style-type: none"> — forwards — backwards — upwards — downwards — at the side | 0 mm |
| <ul style="list-style-type: none"> • for live parts <ul style="list-style-type: none"> — forwards — backwards — upwards — downwards — at the side | 0 mm |
| <ul style="list-style-type: none"> • for live parts <ul style="list-style-type: none"> — forwards — backwards — upwards — downwards — at the side | 0 mm |
| <ul style="list-style-type: none"> • for live parts <ul style="list-style-type: none"> — forwards — backwards — upwards — downwards — at the side | 0 mm |
| <ul style="list-style-type: none"> • for live parts <ul style="list-style-type: none"> — forwards — backwards — upwards — downwards — at the side | 0 mm |
| <ul style="list-style-type: none"> • for live parts <ul style="list-style-type: none"> — forwards — backwards — upwards — downwards — at the side | 0 mm |
| Ambient conditions | |
| installation altitude at height above sea level maximum | 2 000 m |
| ambient temperature | |
| <ul style="list-style-type: none"> • during operation | -25 ... +60 °C |
| <ul style="list-style-type: none"> • during storage | -40 ... +85 °C |
| <ul style="list-style-type: none"> • during transport | -40 ... +85 °C |

relative humidity during operation

10 ... 95 %

Approvals Certificates

Environment

General Product Approval

[Environmental Confirmations](#)



EMV

Test Certificates

Maritime application

other



[Type Test Certificates/Test Report](#)



[Confirmation](#)



Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RQ3052-2SM30>

Cax online generator


<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RQ3052-2SM30>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RQ3052-2SM30>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RQ3052-2SM30&lang=en



last modified:

4/9/2026

