

LED, base BA15d, yellow, 115 V AC, accessory for signaling columns, with diameter 50 mm and 70 mm



Figure similar

product brand name	SIRIUS
product designation	LED
<b>General technical data</b>	
type of voltage of the operating voltage	AC
operating voltage	
• 1 at AC at 50 Hz rated value	115 V
• 1 at AC at 60 Hz rated value	115 V
relative positive tolerance of the operating voltage	10 %
relative negative tolerance of the operating voltage	-15 %
reference code according to EN 61346-2	P
<b>Lamp</b>	
type of light source	LED
light intensity	0.9 cd
socket design	BA 15d
<b>Enclosure</b>	
height	45 mm
width	20 mm
outer diameter of the signal column element	70 mm
color	yellow
<b>Ambient conditions</b>	
ambient temperature during operation	-20 ... +60 °C
<b>Approvals Certificates</b>	
General Product Approval	other



[Confirmation](#)



[Confirmation](#)

[Confirmation](#)

other	Environment
-------	-------------



[Environmental Con-  
firmations](#)



**Further information**

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WD4448-6XD>

Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=8WD4448-6XD>


Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/8WD4448-6XD>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[https://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=8WD4448-6XD&lang=en](https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=8WD4448-6XD&lang=en)

**-P**



last modified:

4/1/2025 