

Siemens
EcoTech



SIMATIC ET 200SP HA, terminal block, type P0, 64 push-in terminals, new load group, width: 45 mm



Figure similar

General information	
Product type designation	Type P0
Product function	
<ul style="list-style-type: none"> I&M data 	Yes
Supply voltage	
Rated value (DC)	24 V
external protection for power supply lines	Yes; 24 V DC / 10 A (MCB with tripping characteristic type B or C, quick-response device protection fuse with sufficient breaking capacity, electronic fuse with characteristic according to type B or C)
Input current	
Current consumption, max.	640 mA; With one 20 mA encoder supply per channel
Encoder supply	
Number of outputs	32
Output voltage (DC)	24 V
24 V encoder supply	
<ul style="list-style-type: none"> Short-circuit protection Output current, max. Output current per module, max. 	Yes; Per output, thermal 20 mA; per output 640 mA
Current carrying capacity	
up to 70 °C, max.	10 A; Permitted load current of the potential group depending on the number of terminal blocks
For process terminals, max.	2 A
Hardware configuration	
Formation of potential groups	
<ul style="list-style-type: none"> support of potential groups New potential group Potential group continued from the left 	Yes Yes No
Slots	
<ul style="list-style-type: none"> Number of slots 	1
Potential separation	
between backplane bus and supply voltage	Yes; 3 000 V DC/1 min, type test
between potential groups (power bus)	Yes; 1 500 V DC/1 min, type test (SELV / PELV to functional ground FE)
between process terminals and supply voltage	Yes; 1 500 V DC/1 min, type test
Ambient conditions	
Ambient temperature during operation	

- horizontal installation, min. -40 °C
- horizontal installation, max. 70 °C
- vertical installation, min. -40 °C
- vertical installation, max. 60 °C

Dimensions

Width	45 mm
Height	175 mm
Depth	77 mm

Weights

Weight, approx.	155 g
-----------------	-------

Classifications

	Version	Classification
eClass	14	27-24-26-07
eClass	12	27-24-26-07
eClass	9.1	27-24-26-07
eClass	9	27-24-26-07
eClass	8	27-24-26-07
eClass	7.1	27-24-26-07
eClass	6	27-24-26-07
ETIM	10	EC001603
ETIM	9	EC001603
ETIM	8	EC001603
ETIM	7	EC001603

Approvals / Certificates

General Product Approval



EG-Konf.

[Miscellaneous](#)



UL



RCM

General Product Approval



[China RoHS](#)

[Miscellaneous](#)



EG-Konf.

[Manufacturer Declaration](#)



For use in hazardous locations



IECEX

[Declaration of Conformity](#)



CCC



UL



ATEX



IECEX

For use in hazardous locations

Maritime application

[Miscellaneous](#)



ABS



BUREAU VERITAS



DNV



LRS

[NK / Nippon Kaiji Kyokai](#)

Maritime application

Environment



[CCS \(China Classification Society\)](#)



last modified:

10/23/2025