

PSN130S 8 A 120 V/230 V AC IP20 Power supply unit 30 V, for AS-i without AS-i data decoupling IN: 120 V / 230 V AC OUT: 30 V DC, 8 A, IP20 with integrated Overload detection with signaling contact

Efficiency/ heat loss		
power loss [W] maximum	W	25
Safety related data		
protection class IP		IP20
Ambient conditions		
ambient temperature		
• during operation	°C	-20 ... +70
• during storage	°C	-40 ... +85
fastening method		fixing on standard mounting rail DIN EN 59 022-35 x 7.5 mm snap-on
width	mm	70
height	mm	125
depth	mm	125

Certificates/ approvals	
Environment	General Product Approval



[Environmental Confirmations](#)



EMV	Maritime application	other
-----	----------------------	-------



[Confirmation](#)



Approvals Certificates		
Environmental Product Declaration		
• global warming potential [CO2 eq] / during manufacturing		20.7 kg
• global warming potential [CO2 eq] / during sales		0.127 kg
• global warming potential [CO2 eq] / during operation		763 kg
• global warming potential [CO2 eq] / after end of life		0.565 kg
• global warming potential [CO2 eq] / total		785 kg

Further information

Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage
<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)
<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RX9513-0AA00>

Cax online generator
<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RX9513-0AA00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/3RX9513-0AA00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RX9513-0AA00&lang=en

last modified: 4/4/2026

