



SIMATIC S7-400, FM458-1 DP application group for SIMATIC S7-400

Supply voltage	
Rated value (DC)	
• 5 V DC	Yes
• 24 V DC	Yes
permissible range (ripple included), lower limit (DC)	4.8 V
permissible range (ripple included), upper limit (DC)	5.25 V
Input current	
Current consumption, typ.	1.5 A
Current consumption, max.	3 A
Memory	
Backup	
• present	Yes; SRAM
Battery	
Backup battery	
• Backup current, max.	15 μ A
Time of day	
Clock	
• Hardware clock (real-time)	Yes
• Resolution	500 ms
Digital inputs	
Number of digital inputs	8; Connector X2
Input voltage	
• Rated value (DC)	24 V
• for signal "0"	-1 to +6V
• for signal "1"	13.5 to 33V
Input current	
• for signal "0", max. (permissible quiescent current)	0 mA
• for signal "1", typ.	3 mA; at 24 V
Input delay (for rated value of input voltage)	
for standard inputs	
— at "0" to "1", max.	5 μ s
Protocols	
PROFIBUS DP	
Services	
— Equidistance	Yes; With connection to interrupt tasks
— Direct data exchange (slave-to-slave communication)	Yes
Interrupts/diagnostics/status information	
Alarms	Yes

Potential separation

Potential separation digital inputs

- Potential separation digital inputs No; only via optional interface modules

Weights

Weight, approx. 1 000 g

Classifications

	Version	Classification
eClass	14	27-24-22-05
eClass	12	27-24-22-05
eClass	9.1	27-24-22-05
eClass	9	27-24-22-05
eClass	8	27-24-22-05
eClass	7.1	27-24-22-05
eClass	6	27-24-22-05
ETIM	10	EC001422
ETIM	9	EC001422
ETIM	8	EC001422
ETIM	7	EC001422
IDEA	4	3567
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval



[Miscellaneous](#)



General Product Approval **EMV** For use in hazardous locations

[China RoHS](#)



[Miscellaneous](#)

For use in hazardous locations **Maritime application**



[CCC-Ex](#)



last modified:

7/1/2025