



SIMATIC ET 200SP HA, 5 TM covers, 22.5 mm, for protection of I/O empty slots

General information																																					
Product type designation	TM cover																																				
Ambient conditions																																					
Ambient temperature during operation																																					
• min.	-40 °C																																				
• max.	70 °C																																				
• horizontal installation, min.	-40 °C																																				
• horizontal installation, max.	70 °C																																				
• vertical installation, min.	-40 °C																																				
• vertical installation, max.	70 °C																																				
Dimensions																																					
Width	22.5 mm																																				
Height	115 mm																																				
Depth	69 mm																																				
Weights																																					
Weight, approx.	40 g																																				
Classifications																																					
	<table border="1"> <thead> <tr> <th></th> <th>Version</th> <th>Classification</th> </tr> </thead> <tbody> <tr> <td>eClass</td> <td>14</td> <td>27-24-26-92</td> </tr> <tr> <td>eClass</td> <td>12</td> <td>27-24-26-92</td> </tr> <tr> <td>eClass</td> <td>9.1</td> <td>27-24-26-92</td> </tr> <tr> <td>eClass</td> <td>9</td> <td>27-24-26-92</td> </tr> <tr> <td>eClass</td> <td>8</td> <td>27-24-26-92</td> </tr> <tr> <td>eClass</td> <td>7.1</td> <td>27-24-26-92</td> </tr> <tr> <td>eClass</td> <td>6</td> <td>27-24-26-92</td> </tr> <tr> <td>ETIM</td> <td>10</td> <td>EC002584</td> </tr> <tr> <td>ETIM</td> <td>9</td> <td>EC002584</td> </tr> <tr> <td>ETIM</td> <td>8</td> <td>EC002584</td> </tr> <tr> <td>ETIM</td> <td>7</td> <td>EC002584</td> </tr> </tbody> </table>		Version	Classification	eClass	14	27-24-26-92	eClass	12	27-24-26-92	eClass	9.1	27-24-26-92	eClass	9	27-24-26-92	eClass	8	27-24-26-92	eClass	7.1	27-24-26-92	eClass	6	27-24-26-92	ETIM	10	EC002584	ETIM	9	EC002584	ETIM	8	EC002584	ETIM	7	EC002584
	Version	Classification																																			
eClass	14	27-24-26-92																																			
eClass	12	27-24-26-92																																			
eClass	9.1	27-24-26-92																																			
eClass	9	27-24-26-92																																			
eClass	8	27-24-26-92																																			
eClass	7.1	27-24-26-92																																			
eClass	6	27-24-26-92																																			
ETIM	10	EC002584																																			
ETIM	9	EC002584																																			
ETIM	8	EC002584																																			
ETIM	7	EC002584																																			
Approvals / Certificates																																					
General Product Approval																																					



last modified:

7/3/2025 