



Figure similar

SIMATIC ET 200SP HA, holder module IM single, support for holding one interface module of the SIMATIC ET 200SP HA, including server module

General information	
Product type designation	IM carrier module, single
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>	Yes; Asset data
Supply voltage	
Rated value (DC)	24 V
Hardware configuration	
Slots	
<ul style="list-style-type: none"> <li>Number of slots</li> </ul>	1
Potential separation	
between backplane bus and supply voltage	Yes
Isolation	
Isolation tested with	1 500 V DC/1 min, type test
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> <li>horizontal installation, min.</li> <li>horizontal installation, max.</li> <li>vertical installation, min.</li> <li>vertical installation, max.</li> </ul>	-40 °C 70 °C -40 °C 60 °C
Dimensions	
Width	100 mm
Height	204 mm
Depth	35 mm; measured without power plug
Weights	
Weight, approx.	250 g

Classifications		
	Version	Classification
eClass	14	27-24-26-07
eClass	12	27-24-26-07
eClass	9.1	27-24-26-07
eClass	9	27-24-26-07
eClass	8	27-24-26-07
eClass	7.1	27-24-26-07

eClass	6	27-24-26-07
ETIM	10	EC001603
ETIM	9	EC001603
ETIM	8	EC001603
ETIM	7	EC001603

Approvals / Certificates

General Product Approval



[Miscellaneous](#)



[Declaration of Conformity](#)



General Product Approval



[China RoHS](#)



[Miscellaneous](#)



[Manufacturer Declaration](#)

For use in hazardous locations



[Declaration of Conformity](#)



For use in hazardous locations

Maritime application

[Miscellaneous](#)



[NK / Nippon Kaiji Kyokai](#)

Maritime application

Environment



[CCS \(China Classification Society\)](#)



last modified:

10/23/2025