

Siemens  
EcoTech



SIMATIC ET 200SP HA, carrier module 8-fold carrier for holding 8 I/O modules of the ET 200SP HA



Figure similar

General information		
Product type designation	Carrier module 8 times	
Product function		
• I&M data	Yes; Asset data	
Hardware configuration		
Formation of potential groups		
• support of potential groups	Yes	
Slots		
• Number of slots	8	
Potential separation		
between backplane bus and supply voltage	Yes; 4 200 V DC/1 min, type test	
between the potential groups	Yes; 3 510 V AC/ 5 s, type test (between the power supply groups; due to isolating distance (increased isolation) for future ÜK-III requirement of F technology)	
Isolation		
Isolation tested with	1 500 V DC/1 min, type test (between backplane bus and functional ground)	
Ambient conditions		
Ambient temperature during operation		
• horizontal installation, min.	-40 °C	
• horizontal installation, max.	70 °C	
• vertical installation, min.	-40 °C	
• vertical installation, max.	60 °C	
Dimensions		
Width	187.5 mm; 180 mm when installed	
Height	203 mm	
Depth	79 mm	
Weights		
Weight, approx.	450 g	
Classifications		
	<b>Version</b>	<b>Classification</b>
eClass	14	27-24-26-07
eClass	12	27-24-26-07
eClass	9.1	27-24-26-07
eClass	9	27-24-26-07

eClass	8	27-24-26-07
eClass	7.1	27-24-26-07
eClass	6	27-24-26-07
ETIM	10	EC001603
ETIM	9	EC001603
ETIM	8	EC001603
ETIM	7	EC001603

Approvals / Certificates

General Product Approval



[Miscellaneous](#)



[Declaration of Conformity](#)



General Product Approval



[China RoHS](#)

[Miscellaneous](#)



[Manufacturer Declaration](#)



For use in hazardous locations



[Declaration of Conformity](#)



For use in hazardous locations

Maritime application

[Miscellaneous](#)



[NK / Nippon Kaiji Kyokai](#)

Maritime application

Environment



[CCS \(China Classification Society\)](#)

Siemens EcoTech



last modified:

10/23/2025