



SIMATIC ET 200AL, PROFIBUS interface module IM 157-1 DP, degree of protection IP67; product phase-out planned - see SIOS 109989704

General information	
Product type designation	IM 157-1 DP
HW functional status	FS02
Firmware version	V1.0.x
Vendor identification (VendorID)	81A9H
Product function	
<ul style="list-style-type: none"> I&M data 	Yes; I&M0 to I&M3
Engineering with	
<ul style="list-style-type: none"> STEP 7 TIA Portal configurable/integrated from version 	STEP 7 V13 SP1 or higher
<ul style="list-style-type: none"> STEP 7 configurable/integrated from version 	From V5.5 SP4 Hotfix 3
<ul style="list-style-type: none"> PROFIBUS from GSD version/GSD revision 	GSD as of Revision 5
Configuration control	
via dataset	Yes
Supply voltage	
power supply according to NEC Class 2 required	No
Load voltage 1L+	
<ul style="list-style-type: none"> Rated value (DC) 	24 V
<ul style="list-style-type: none"> permissible range, lower limit (DC) 	20.4 V
<ul style="list-style-type: none"> permissible range, upper limit (DC) 	28.8 V
<ul style="list-style-type: none"> Reverse polarity protection 	Yes; against destruction
Input current	
Current consumption (rated value)	50 mA
from load voltage 1L+ (unswitched voltage)	4 A; Maximum value
from load voltage 2L+, max.	4 A; Maximum value
Power loss	
Power loss, typ.	1.7 W
Address area	
Address space per station	
<ul style="list-style-type: none"> Address space per station, max. 	244 byte
Interfaces	
Number of PROFIBUS interfaces	1
1. Interface	
Interface type	PROFIBUS DP
Interface types	
<ul style="list-style-type: none"> RS 485 	Yes
<ul style="list-style-type: none"> M12 port 	Yes; 2x M12 B-coded
Protocols	
<ul style="list-style-type: none"> PROFIBUS DP device 	Yes

Interface types			
RS 485			
• Transmission rate, max.		12 Mbit/s	
Protocols			
Supports protocol for PROFINET IO		No	
PROFIsafe		No	
PROFIBUS		Yes	
EtherNet/IP		No	
PROFIBUS DP			
Services			
— SYNC capability		Yes	
— FREEZE capability		Yes	
— Direct data exchange (slave-to-slave communication)		Yes	
— DPV0		Yes	
— DPV1		Yes	
Interrupts/diagnostics/status information			
Diagnostics function		Yes	
Alarms			
• Diagnostic alarm		Yes	
Diagnostics indication LED			
• RUN LED		Yes; green LED	
• ERROR LED		Yes; red LED	
• MAINT LED		Yes; Yellow LED	
• Connection display DP		Yes; green LED	
Potential separation			
between the load voltages		Yes	
between PROFIBUS DP and all other circuit components		Yes	
Isolation			
Isolation tested with		707 V DC (type test)	
Degree and class of protection			
IP degree of protection		IP65/67	
Standards, approvals, certificates			
Suitable for safety-related tripping of standard modules		Yes; from FS01	
Highest safety class achievable for safety-related tripping of standard modules			
• Performance level according to ISO 13849-1		PL d	
• Category according to ISO 13849-1		Cat. 3	
• SIL acc. to IEC 62061		SIL 2	
• remark on safety-oriented shutdown		https://support.industry.siemens.com/cs/de/en/view/39198632	
Ambient conditions			
Ambient temperature during operation			
• min.		-30 °C	
• max.		55 °C	
Connection method			
Design of electrical connection for supply voltage		M8, 4-pole	
ET-Connection			
• ET-Connection		M8, 4-pin, shielded	
Dimensions			
Width		45 mm	
Height		159 mm	
Depth		46 mm	
Weights			
Weight, approx.		211 g	
Classifications			
		Version	Classification
	eClass	14	27-24-26-08
	eClass	12	27-24-26-08
	eClass	9.1	27-24-26-08

eClass	9	27-24-26-08
eClass	8	27-24-26-08
eClass	7.1	27-24-26-08
eClass	6	27-24-26-08
ETIM	10	EC001604
ETIM	9	EC001604
ETIM	8	EC001604
ETIM	7	EC001604
IDEA	4	3564
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

[Miscellaneous](#)

[Manufacturer Declaration](#)



General Product Approval



[China RoHS](#)

[Manufacturer Declaration](#)



EMV **Maritime application**



[NK / Nippon Kaiji Kyokai](#)

Maritime application **other** **Industrial Communication**



[CCS \(China Classification Society\)](#)

[KR \(Korean Register of Shipping\)](#)



last modified:

10/23/2025