



SIMATIC S7-1200, EMS400S, EMS400S diagnostics unit

Supply voltage	
Rated value (DC)	24 V
Interfaces	
Number of interfaces	2; Differential, 48 V AC /USB
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Potential separation	
Potential separation exists	Yes
Standards, approvals, certificates	
CE mark	Yes
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	50 °C
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	50 °C

Classifications			
		Version	Classification
	eClass	14	27-24-22-92
	eClass	12	27-24-22-92
	eClass	9.1	27-24-22-92
	eClass	9	27-24-22-92
	eClass	8	27-24-92-90
	eClass	7.1	27-24-92-90
	eClass	6	27-24-92-90
	ETIM	10	EC002584
	ETIM	9	EC002584
	ETIM	8	EC002584
	ETIM	7	EC002584
	IDEA	4	3552
	UNSPSC	15	32-15-17-03

Approvals / Certificates	
General Product Approval	



EG-Konf.

[Manufacturer Declaration](#)



[China RoHS](#)



EG-Konf.



EMV



EG-Konf.



last modified:

7/17/2025