



Figure similar

spare part SIMATIC S7-1500, CM PTP RS-232 HF communications module for serial connection RS-232, Freeport, 3964 (R), USS, Modbus RTU master, device, 115200 Kbps, 9-pin D-sub plug

General information	
Product type designation	CM PtP RS 232 HF
Product function	
<ul style="list-style-type: none"> I&M data Fast startup 	Yes; I&M 0 Yes
Engineering with	
<ul style="list-style-type: none"> STEP 7 TIA Portal configurable/integrated from version STEP 7 configurable/integrated from version PROFIBUS from GSD version/GSD revision PROFINET from GSD version/GSD revision 	V12 / V12 V5.5 SP2 with GSD file - / - V2.3 / -
Installation type/mounting	
Rail mounting	Yes; S7-1500 mounting rail
Input current	
Current consumption (rated value)	50 mA; From the backplane bus
Power	
Power consumption from the backplane bus	0.75 W
Power loss	
Power loss, typ.	0.6 W
Address area	
Address space per module	
<ul style="list-style-type: none"> Inputs 	8 byte
Interface types	
RS 232	
<ul style="list-style-type: none"> Transmission rate, max. Cable length, max. RS 232 auxiliary signals 	115.2 kbit/s 15 m RTS, CTS, DTR, DSR, RI, DCD
Protocols	
Integrated protocols	
Freeport	
<ul style="list-style-type: none"> Telegram length, max. Bits per character Number of stop bits Parity 	4 kbyte 7 or 8 1 or 2 bit None, even, odd, always 1, always 0, any
3964 (R)	
<ul style="list-style-type: none"> Telegram length, max. Bits per character Number of stop bits Parity 	4 kbyte 7 or 8 1 or 2 bit None, even, odd, always 1, always 0, any

Modbus RTU master		
— Address area	1 to 247, extended 1 to 65535	
— max. number of devices	1	
Modbus RTU device		
— Address area	1 to 247, extended 1 to 65535	
Telegram buffer		
• Buffer memory for telegrams	8 kbyte	
• Number of telegrams which can be buffered	255	
Interrupts/diagnostics/status information		
Diagnostics function	Yes	
Alarms		
• Diagnostic alarm	Yes	
• Hardware interrupt	No	
Diagnoses		
• Wire break	Yes	
Diagnostics indication LED		
• RUN LED	Yes; green LED	
• ERROR LED	Yes; red LED	
• Receive RxD	Yes; Yellow LED	
• Transmit TxD	Yes; Yellow LED	
Potential separation		
between backplane bus and interface	Yes	
Isolation		
Isolation tested with	707 V DC (type test)	
Ambient conditions		
Ambient temperature during operation		
• horizontal installation, min.	0 °C	
• horizontal installation, max.	60 °C	
• vertical installation, min.	0 °C	
• vertical installation, max.	40 °C	
Altitude during operation relating to sea level		
• Installation altitude above sea level, max.	5 000 m; restrictions for installation altitudes > 2 000 m, see ET 200MP system manual	
Decentralized operation		
to SIMATIC S7-300	Yes	
to SIMATIC S7-400	Yes	
to SIMATIC S7-1500	Yes	
to standard PROFINET controller	Yes	
Dimensions		
Width	35 mm	
Height	147 mm	
Depth	127 mm	
Weights		
Weight, approx.	0.22 kg	
Classifications		
	Version	Classification
eClass	14	27-24-22-08
eClass	12	27-24-22-08
eClass	9.1	27-24-22-08
eClass	9	27-24-22-08
eClass	8	27-24-22-08
eClass	7.1	27-24-22-08
eClass	6	27-24-22-08
ETIM	10	EC001423
ETIM	9	EC001423
ETIM	8	EC001423
ETIM	7	EC001423

IDEA	4	3564
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

[Miscellaneous](#)

[Manufacturer Declaration](#)



General Product Approval | **For use in hazardous locations**



[China RoHS](#)



[EM](#)



For use in hazardous locations

[EM](#)

[CCC-Ex](#)



[Type Examination Certificate](#)



[Miscellaneous](#)

For use in hazardous locations | **Maritime application**

[CCC-Ex](#)



Maritime application



[CCS \(China Classification Society\)](#)

[KR \(Korean Register of Shipping\)](#)

last modified:

10/23/2025