

***** spare part ***** complete set of screw terminals two-row 2x2(24 V) and single-row 1x6(GND) and single-row 4x8(IO) for SIMATIC CFU

General information	
Product description	Complete set of double-row screw-type terminals 2x2 (24 V) and single-row 1x6 (GND) and 4x8 (IO) for SIMATIC CFU
Ambient conditions	
Ambient temperature during operation	
• min.	-40 °C
• max.	70 °C
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	85 °C
Connection method	
Spur line	
• Type of cable	Type A
• Conductor cross-section, min.	0.2 mm ²
• Conductor cross-section, max.	2.5 mm ²
Weights	
Weight, approx.	90 g

	Version	Classification
eClass	14	27-23-02-92
eClass	12	27-23-02-92
eClass	9.1	27-23-02-92
eClass	9	27-23-02-92
eClass	8	27-23-92-90
eClass	7.1	27-23-92-90
eClass	6	27-23-92-90
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584
IDEA	4	3552
UNSPSC	15	32-15-17-03

Approvals / Certificates	
General Product Approval	For use in hazardous locations



[China RoHS](#)

[Manufacturer Declaration](#)

[Type Examination Certificate](#)



For use in hazardous locations

[CCC-Ex](#)



IECEX

last modified:

5/29/2025 