



SIMATIC S7-400, interface module IF963-RS232 with RS232 interface for PTP coupling with CP441 AB CP 441- AA05

Input current	
Current consumption, max.	15 mA
Power loss	
Power loss, typ.	0.05 W
Interfaces	
Point-to-point connection	
• Transmission rate, max.	115.2 kbit/s
• Cable length, max.	15 m
Dimensions	
Width	19 mm
Height	67 mm
Depth	87 mm
Weights	
Weight, approx.	80 g

Classifications	Version	Classification
eClass	14	27-24-22-08
eClass	12	27-24-22-08
eClass	9.1	27-24-22-08
eClass	9	27-24-22-08
eClass	8	27-24-22-08
eClass	7.1	27-24-22-08
eClass	6	27-24-22-08
ETIM	10	EC001423
ETIM	9	EC001423
ETIM	8	EC001423
ETIM	7	EC001423
IDEA	4	3564
UNSPSC	15	32-15-17-05

Approvals / Certificates	
General Product Approval	



[Miscellaneous](#)



General Product Approval For use in hazardous locations

[Miscellaneous](#)

[China RoHS](#)



IECEX



ATEX

[EM](#)



CCC

For use in hazardous locations Maritime application



IECEX

[Type Examination Certificate](#)



ATEX



BUREAU VERITAS



DNV



LRS

Maritime application



RINA

[CCS \(China Classification Society\)](#)

last modified:

6/7/2025