



SIMATIC S7-400, interface module IF963-X27 with RS422/RS485 interface for PTP coupling with CP441 AB CP 441- AA05

Input current	
Current consumption, max.	41 mA
Power loss	
Power loss, typ.	0.14 W
Interfaces	
Point-to-point connection	
• Transmission rate, max.	115.2 kbit/s
• Cable length, max.	1 200 m; at 19 200 bps
Dimensions	
Width	19 mm
Height	67 mm
Depth	87 mm
Weights	
Weight, approx.	80 g

Classifications			
		Version	Classification
	eClass	14	27-24-22-08
	eClass	12	27-24-22-08
	eClass	9.1	27-24-22-08
	eClass	9	27-24-22-08
	eClass	8	27-24-22-08
	eClass	7.1	27-24-22-08
	eClass	6	27-24-22-08
	ETIM	10	EC001423
	ETIM	9	EC001423
	ETIM	8	EC001423
	ETIM	7	EC001423
	IDEA	4	3564
	UNSPSC	15	32-15-17-05

Approvals / Certificates	
General Product Approval	



[Miscellaneous](#)



General Product Approval | For use in hazardous locations

[Miscellaneous](#)

[China RoHS](#)



IECEX



ATEX

[EM](#)



CCC

For use in hazardous locations | Maritime application



IECEX

[Type Examination Certificate](#)



ATEX



DNV



LRS



RINA

Maritime application

[CCS \(China Classification Society\)](#)

last modified:

6/7/2025