



Figure similar

spare part SIMATIC S7-300, connection IM 361 in expansion rack for connection to central rack (IM360), supply voltage 24 V DC, with C-bus

Supply voltage	
Rated value (DC)	Yes
• 24 V DC	
Input current	
from supply voltage L+, max.	500 mA
Power loss	
Power loss, typ.	5 W
Hardware configuration	
Number of interfaces per CPU, max.	3
Dimensions	
Width	80 mm
Height	125 mm
Depth	120 mm
Weights	
Weight, approx.	505 g

Classifications			
		Version	Classification
	eClass	14	27-24-22-08
	eClass	12	27-24-22-08
	eClass	9.1	27-24-22-08
	eClass	9	27-24-22-08
	eClass	8	27-24-22-08
	eClass	7.1	27-24-22-08
	eClass	6	27-24-22-08
	ETIM	10	EC001423
	ETIM	9	EC001423
	ETIM	8	EC001423
	ETIM	7	EC001423
	IDEA	4	3564
	UNSPSC	15	32-15-17-05

Approvals / Certificates	
General Product Approval	



[Manufacturer Declaration](#)



General Product Approval EMV For use in hazardous locations

[Manufacturer Declaration](#)



[EM](#)



For use in hazardous locations Maritime application



[Miscellaneous](#)

[CCC-Ex](#)



Maritime application



[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)

last modified:

4/7/2025