



Plug-in relay, 3 changeover contacts Relay with LED 28 mm, 24 V DC

product brand name	SIRIUS
product designation	Plug-in relay
product type designation	LZX
General technical data	
consumed active power	1 200 mW
percental drop-out voltage related to the input voltage	10 %
shock resistance according to IEC 60068-2-27	10 g / 11 ms
vibration resistance according to IEC 60068-2-6	30 ... 150 Hz: 2 g
operating frequency without load	6 000 1/h
operating frequency with load	1 200 1/h
switching behavior	monostable
mechanical service life (operating cycles) typical	20 000 000
electrical endurance (operating cycles) at AC-15 at 230 V typical	300 000
thermal current	10 A
reference code according to IEC 81346-2	K
Substance Prohibitance (day/month/year)	05/01/2012
Net Weight	0.086 kg
Control circuit/ Control	
control supply voltage at DC rated value	24 V
operating range factor control supply voltage rated value at DC	
• initial value	0.9
• full-scale value	1.4
Switching Function	
design of the switching function	changeover switch
Mechanical data	
product component plug-in socket	No
design of the relay operating mechanism	poled
Auxiliary circuit	
type of switching contact	Changeover contact
material of switching contacts	AgNi 90/10
number of NC contacts for auxiliary contacts	0
number of NO contacts for auxiliary contacts	0
number of CO contacts for auxiliary contacts	3
Main circuit	
type of voltage	DC
Connections/ Terminals	
product function removable terminal	No
Installation/ mounting/ dimensions	

mounting position	any
fastening method	base mounting
height	36.5 mm
width	35.5 mm
depth	69 mm

Ambient conditions

ambient temperature	
<ul style="list-style-type: none"> during operation 	-40 ... +60 °C
<ul style="list-style-type: none"> during storage 	-40 ... +60 °C
<ul style="list-style-type: none"> during transport 	-40 ... +60 °C

Approvals Certificates

Environment	General Product Approval
-------------	--------------------------

[Environmental Con-
firmations](#)



Maritime application	other
----------------------	-------



LRS

[Confirmation](#)

[Confirmation](#)



Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=LZX:MT323024>

Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=LZX:MT323024>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/LZX:MT323024>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=LZX:MT323024&lang=en



