



Load feeder fuseless, Direct-on-line starting 400 V AC, Size S00 1.10...1.60 A 24 V DC Spring-type terminal for 60 mm busbar systems (also fulfills type of coordination 1) Type of coordination 2, I<sub>q</sub> = 150 kA 1 NO (contactor)

|  |  |
|--|--|
| <b>product brand name</b>  | SIRIUS   |
| <b>product designation</b>   | Direct (on-line) starter   |
| <b>design of the product</b>   | for 60 mm busbars  |
| <b>product type designation</b>  | 3RA21  |
| <b>manufacturer's article number</b>   |  |
| <ul style="list-style-type: none"> <li>• of the supplied contactor</li> <li>• of the supplied circuit-breakers</li> <li>• of the supplied busbar adapter</li> <li>• of the supplied link module</li> </ul> | <a href="#">3RT2015-2BB41</a><br><a href="#">3RV2011-1AA20</a><br><a href="#">8US1251-5DT11</a><br><a href="#">3RA2911-2AA00</a> |
| <b>General technical data</b>  |  |
| <b>size of the circuit-breaker</b>   | S00  |
| <b>size of load feeder</b>   | S00  |
| <b>power loss [W] for rated value of the current</b>   |  |
| <ul style="list-style-type: none"> <li>• at AC in hot operating state per pole</li> <li>• without load current share typical</li> </ul>  | 2.6 W<br>4 W   |
| <b>type of calculation of power loss current-dependent</b>   | quadratic  |
| insulation voltage with degree of pollution 3 at AC rated value  | 690 V  |
| <b>surge voltage resistance rated value</b>  | 6 kV   |
| <b>degree of protection NEMA rating</b>  | other  |
| <b>shock resistance according to IEC 60068-2-27</b>  | 6 g / 11 ms  |
| mechanical service life (operating cycles) of contactor typical  | 30 000 000   |
| <b>type of coordination</b>  | 2  |
| <b>reference code according to IEC 81346-2:2019</b>  | Q  |
| <b>Substance Prohibitance (day/month/year)</b>   | 10/01/2009   |
| <b>SVHC substance name</b>   | Lead CAS-No. 7439-92-1   |
| <b>Net Weight</b>  | 1.21 kg  |
| <b>Ambient conditions</b>  |  |
| <b>ambient temperature</b>   |  |
| <ul style="list-style-type: none"> <li>• during operation</li> <li>• during storage</li> <li>• during transport</li> </ul>   | -20 ... +60 °C<br>-50 ... +80 °C<br>-50 ... +80 °C   |
| <b>temperature compensation</b>  | -20 ... +60 °C   |
| relative humidity during operation   | 10 ... 95 %  |
| <b>Main circuit</b>  |  |
| <b>number of poles for main current circuit</b>  | 3  |
| <b>design of the switching contact</b>   | electromechanical  |
| <b>adjustable current response value current of the current-dependent overload release</b>   | 1.1 ... 1.6 A  |
| <b>operating voltage</b>   |  |

|   |  |
|---|--|
| <ul style="list-style-type: none"> <li>• rated value</li> </ul>   | 690 V                                  |
| <ul style="list-style-type: none"> <li>• at AC-3 rated value maximum</li> </ul>   | 690 V                                  |
| <ul style="list-style-type: none"> <li>• at AC-3e rated value maximum</li> </ul>  | 690 V                                  |
| <b>operating frequency rated value</b>  | 50 ... 60 Hz                           |
| <b>operational current</b>  |  |
| <ul style="list-style-type: none"> <li>• at AC-3 at 400 V rated value</li> </ul>  | 1.6 A                                  |
| <ul style="list-style-type: none"> <li>• at AC-3e at 400 V rated value</li> </ul>   | 1.6 A                                  |
| <b>operating power</b>  |  |
| <ul style="list-style-type: none"> <li>• at AC-3 <ul style="list-style-type: none"> <li>— at 400 V rated value</li> </ul> </li> </ul>                   | 550 W                                  |
| <ul style="list-style-type: none"> <li>• at AC-3e <ul style="list-style-type: none"> <li>— at 400 V rated value</li> </ul> </li> </ul>                  | 550 W                                  |
| <b>Control circuit/ Control</b>   |  |
| <b>type of voltage of the control supply voltage</b>  | DC                                     |
| <b>control supply voltage at DC rated value</b>   | 24 V                                   |
| <b>holding power of magnet coil at DC</b>   | 4 W                                    |
| <b>Auxiliary circuit</b>  |  |
| <b>product extension auxiliary switch</b>   | Yes                                    |
| <b>Protective and monitoring functions</b>  |  |
| <b>trip class</b>   | CLASS 10                               |
| <b>design of the overload release</b>   | thermal (bimetallic)                   |
| response value current of instantaneous short-circuit trip unit   | 21 A                                   |
| <b>UL/CSA ratings</b>   |  |
| <b>full-load current (FLA) for 3-phase AC motor</b>   |  |
| <ul style="list-style-type: none"> <li>• at 480 V rated value</li> </ul>  | 1.6 A                                  |
| <ul style="list-style-type: none"> <li>• at 600 V rated value</li> </ul>  | 1.6 A                                  |
| <b>yielded mechanical performance [hp]</b>  |  |
| <ul style="list-style-type: none"> <li>• for single-phase AC motor <ul style="list-style-type: none"> <li>— at 230 V rated value</li> </ul> </li> </ul> | 0.1 hp                                 |
| <ul style="list-style-type: none"> <li>• for 3-phase AC motor <ul style="list-style-type: none"> <li>— at 220/230 V rated value</li> </ul> </li> </ul>  | 0.5 hp                                 |
| <ul style="list-style-type: none"> <li>— at 460/480 V rated value</li> </ul>  | 1 hp                                   |
| <ul style="list-style-type: none"> <li>— at 575/600 V rated value</li> </ul>  | 1 hp                                   |
| <b>Short-circuit protection</b>   |  |
| <b>product function short circuit protection</b>  | Yes                                    |
| <b>design of the short-circuit trip</b>   | magnetic                               |
| <b>conditional short-circuit current (I<sub>q</sub>)</b>  |  |
| <ul style="list-style-type: none"> <li>• at 400 V according to IEC 60947-4-1 rated value</li> </ul>   | 150 000 A                              |
| <b>Installation/ mounting/ dimensions</b>   |  |
| <b>mounting position</b>  | vertical                               |
| <b>fastening method</b>   | for snapping onto 60 mm busbar systems |
| <b>height</b>   | 260 mm                                 |
| <b>width</b>  | 45 mm                                  |
| <b>depth</b>  | 155 mm                                 |
| <b>required spacing</b>   |  |
| <ul style="list-style-type: none"> <li>• for grounded parts <ul style="list-style-type: none"> <li>— forwards</li> </ul> </li> </ul>                    | 20 mm                                  |
| <ul style="list-style-type: none"> <li>— backwards</li> </ul>   | 0 mm                                   |
| <ul style="list-style-type: none"> <li>— upwards</li> </ul>   | 50 mm                                  |
| <ul style="list-style-type: none"> <li>— at the side</li> </ul>   | 20 mm                                  |
| <ul style="list-style-type: none"> <li>— downwards</li> </ul>   | 10 mm                                  |
| <ul style="list-style-type: none"> <li>• for live parts <ul style="list-style-type: none"> <li>— forwards</li> </ul> </li> </ul>                        | 20 mm                                  |
| <ul style="list-style-type: none"> <li>— backwards</li> </ul>   | 0 mm                                   |
| <ul style="list-style-type: none"> <li>— upwards</li> </ul>   | 50 mm                                  |
| <ul style="list-style-type: none"> <li>— downwards</li> </ul>   | 10 mm                                  |
| <ul style="list-style-type: none"> <li>— at the side</li> </ul>   | 20 mm                                  |
| <b>Connections/ Terminals</b>   |  |

|   |  |
|---|--|
| <b>type of electrical connection</b>  |  |
| <ul style="list-style-type: none"> <li>for main current circuit</li> <li>for auxiliary and control circuit</li> </ul> | spring-loaded terminals<br>spring-loaded terminals |

**Safety related data**

|   |     |
|---|-----|
| product function suitable for safety function | Yes |
|---|-----|

**Electrical Safety**

|   |  |
|---|--|
| <b>touch protection on the front according to IEC 60529</b> | finger-safe, for vertical contact from the front |
|---|--|

**Communication/ Protocol**

|  |          |
|--|----------|
| <b>protocol is supported</b>   |          |
| <ul style="list-style-type: none"> <li>PROFINET IO protocol</li> <li>PROFIsafe protocol</li> </ul> | No<br>No |
| protocol is supported AS-Interface protocol  | No       |

**Approvals Certificates**

|                    |                                 |                                       |
|--------------------|---------------------------------|---------------------------------------|
| <b>Environment</b> | <b>General Product Approval</b> | <b>For use in hazardous locations</b> |
|--------------------|---------------------------------|---------------------------------------|

[Environmental Confirmations](#)



**Test Certificates**      **Maritime application**

[Type Test Certificates/Test Report](#)

[Special Test Certificate](#)



**Maritime application**      **other**



[Confirmation](#)

[Confirmation](#)



**Railway**      **Dangerous goods**

[Special Test Certificate](#)

[Transport Information](#)

**Further information**

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RA2110-1AH15-1BB4>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RA2110-1AH15-1BB4>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[https://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RA2110-1AH15-1BB4&lang=en](https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RA2110-1AH15-1BB4&lang=en)

Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RA2110-1AH15-1BB4>

Characteristic curves

[https://curves.simaris.siemens.com/curves/<mmp\\_prod\\_noCOMP="HAUPT"></mmp\\_prod\\_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)



last modified:

4/24/2026