



Load feeder fuseless, Direct-on-line starting 400 V AC, Size S0 3.50...5.00 A 24 V DC Spring-type terminal for installation on standard mounting rail (also fulfills type of coordination 1) Type of coordination 2, I<sub>q</sub> = 150 kA 1 NO+1 NC (contactor)

|  |   |
|--|---|
| <b>product brand name</b>  | SIRIUS  |
| <b>product designation</b>   | Direct (on-line) starter  |
| <b>design of the product</b>   | for DIN-rail or screw mounting  |
| <b>product type designation</b>  | 3RA21   |
| <b>manufacturer's article number</b>   |   |
| <ul style="list-style-type: none"> <li>• of the supplied contactor</li> <li>• of the supplied circuit-breakers</li> <li>• of the supplied link module</li> </ul> | <a href="#">3RT2024-2BB40</a><br><a href="#">3RV2021-1FA20</a><br><a href="#">3RA2921-2AA00</a> |
| <b>General technical data</b>  |   |
| <b>size of the circuit-breaker</b>   | S0  |
| <b>size of load feeder</b>   | S0  |
| <b>power loss [W] for rated value of the current</b>   |   |
| <ul style="list-style-type: none"> <li>• at AC in hot operating state per pole</li> <li>• without load current share typical</li> </ul>                          | 2.7 W<br>5.9 W  |
| <b>type of calculation of power loss current-dependent</b>   | quadratic   |
| insulation voltage with degree of pollution 3 at AC rated value  | 690 V   |
| <b>surge voltage resistance rated value</b>  | 6 kV  |
| <b>degree of protection NEMA rating</b>  | other   |
| <b>shock resistance according to IEC 60068-2-27</b>  | 6 g / 11 ms   |
| mechanical service life (operating cycles) of contactor typical  | 10 000 000  |
| <b>type of coordination</b>  | 2   |
| <b>reference code according to IEC 81346-2:2019</b>  | Q   |
| <b>Substance Prohibition (day/month/year)</b>  | 03/01/2017  |
| <b>SVHC substance name</b>   | Lead CAS-No. 7439-92-1  |
| <b>Net Weight</b>  | 1.143 kg  |
| <b>Ambient conditions</b>  |   |
| <b>ambient temperature</b>   |   |
| <ul style="list-style-type: none"> <li>• during operation</li> <li>• during storage</li> <li>• during transport</li> </ul>                                       | -20 ... +60 °C<br>-50 ... +80 °C<br>-50 ... +80 °C  |
| <b>temperature compensation</b>  | -20 ... +60 °C  |
| relative humidity during operation   | 10 ... 95 %   |
| <b>Main circuit</b>  |   |
| <b>number of poles for main current circuit</b>  | 3   |
| <b>design of the switching contact</b>   | electromechanical   |
| <b>adjustable current response value current of the current-dependent overload release</b>   | 3.5 ... 5 A   |
| <b>operating voltage</b>   |   |
| <ul style="list-style-type: none"> <li>• rated value</li> </ul>  | 690 V   |

|   |  |
|---|--|
| <ul style="list-style-type: none"> <li>• at AC-3 rated value maximum</li> </ul>   | 690 V  |
| <ul style="list-style-type: none"> <li>• at AC-3e rated value maximum</li> </ul>  | 690 V  |
| <b>operating frequency rated value</b>  | 50 ... 60 Hz                                   |
| <b>operational current</b>  |  |
| <ul style="list-style-type: none"> <li>• at AC-3 at 400 V rated value</li> </ul>  | 5 A  |
| <ul style="list-style-type: none"> <li>• at AC-3e at 400 V rated value</li> </ul>   | 5 A  |
| <b>operating power</b>  |  |
| <ul style="list-style-type: none"> <li>• at AC-3 <ul style="list-style-type: none"> <li>— at 400 V rated value</li> </ul> </li> </ul>                       | 1 500 W  |
| <ul style="list-style-type: none"> <li>• at AC-3e <ul style="list-style-type: none"> <li>— at 400 V rated value</li> </ul> </li> </ul>                      | 1 500 W  |
| <b>Control circuit/ Control</b>   |  |
| <b>type of voltage of the control supply voltage</b>  | DC   |
| <b>control supply voltage at DC rated value</b>   | 24 V   |
| <b>holding power of magnet coil at DC</b>   | 5.9 W  |
| <b>Auxiliary circuit</b>  |  |
| <b>product extension auxiliary switch</b>   | Yes  |
| <b>Protective and monitoring functions</b>  |  |
| <b>trip class</b>   | CLASS 10                                       |
| <b>design of the overload release</b>   | thermal (bimetallic)                           |
| response value current of instantaneous short-circuit trip unit   | 65 A   |
| <b>UL/CSA ratings</b>   |  |
| <b>full-load current (FLA) for 3-phase AC motor</b>   |  |
| <ul style="list-style-type: none"> <li>• at 480 V rated value</li> </ul>  | 5 A  |
| <ul style="list-style-type: none"> <li>• at 600 V rated value</li> </ul>  | 5 A  |
| <b>yielded mechanical performance [hp]</b>  |  |
| <ul style="list-style-type: none"> <li>• for single-phase AC motor <ul style="list-style-type: none"> <li>— at 110/120 V rated value</li> </ul> </li> </ul> | 0.25 hp  |
| <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>— at 230 V rated value</li> </ul> </li> </ul>                                | 0.5 hp   |
| <ul style="list-style-type: none"> <li>• for 3-phase AC motor <ul style="list-style-type: none"> <li>— at 200/208 V rated value</li> </ul> </li> </ul>      | 1.5 hp   |
| <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>— at 220/230 V rated value</li> </ul> </li> </ul>                            | 1.5 hp   |
| <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>— at 460/480 V rated value</li> </ul> </li> </ul>                            | 3 hp   |
| <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>— at 575/600 V rated value</li> </ul> </li> </ul>                            | 5 hp   |
| <b>Short-circuit protection</b>   |  |
| <b>product function short circuit protection</b>  | Yes  |
| <b>design of the short-circuit trip</b>   | magnetic                                       |
| <b>conditional short-circuit current (I<sub>q</sub>)</b>  |  |
| <ul style="list-style-type: none"> <li>• at 400 V according to IEC 60947-4-1 rated value</li> </ul>   | 150 000 A                                      |
| <b>Installation/ mounting/ dimensions</b>   |  |
| <b>mounting position</b>  | vertical                                       |
| <b>fastening method</b>   | screw and snap-on mounting onto 35 mm DIN rail |
| <b>height</b>   | 243 mm   |
| <b>width</b>  | 45 mm  |
| <b>depth</b>  | 107 mm   |
| <b>required spacing</b>   |  |
| <ul style="list-style-type: none"> <li>• for grounded parts <ul style="list-style-type: none"> <li>— forwards</li> </ul> </li> </ul>                        | 20 mm  |
| <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>— backwards</li> </ul> </li> </ul>   | 0 mm   |
| <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>— upwards</li> </ul> </li> </ul>   | 50 mm  |
| <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>— at the side</li> </ul> </li> </ul>   | 20 mm  |
| <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>— downwards</li> </ul> </li> </ul>   | 10 mm  |
| <ul style="list-style-type: none"> <li>• for live parts <ul style="list-style-type: none"> <li>— forwards</li> </ul> </li> </ul>                            | 20 mm  |
| <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>— backwards</li> </ul> </li> </ul>   | 0 mm   |
| <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>— upwards</li> </ul> </li> </ul>   | 50 mm  |
| <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>— downwards</li> </ul> </li> </ul>   | 10 mm  |
| <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>— at the side</li> </ul> </li> </ul>   | 20 mm  |

## Connections/ Terminals

|   |                         |
|---|-------------------------|
| <b>type of electrical connection</b>  |                         |
| <ul style="list-style-type: none"> <li>• for main current circuit</li> </ul>          | spring-loaded terminals |
| <ul style="list-style-type: none"> <li>• for auxiliary and control circuit</li> </ul> | spring-loaded terminals |

## Safety related data

|   |     |
|---|-----|
| product function suitable for safety function | Yes |
|---|-----|

## Electrical Safety

|   |  |
|---|--|
| <b>touch protection on the front according to IEC 60529</b> | finger-safe, for vertical contact from the front |
|---|--|

## Communication/ Protocol

|  |    |
|--|----|
| <b>protocol is supported</b>   |    |
| <ul style="list-style-type: none"> <li>• PROFINET IO protocol</li> </ul> | No |
| <ul style="list-style-type: none"> <li>• PROFI-safe protocol</li> </ul>  | No |
| protocol is supported AS-Interface protocol                              | No |

## Approvals Certificates

| Environment | General Product Approval | For use in hazardous locations |
|-------------|--------------------------|--------------------------------|
|-------------|--------------------------|--------------------------------|

[Environmental Confirmations](#)



## Test Certificates

Maritime application

[Type Test Certificates/Test Report](#)

[Special Test Certificate](#)



## Maritime application

other



[Confirmation](#)

[Confirmation](#)



## Railway

Dangerous goods

[Special Test Certificate](#)

[Transport Information](#)

## Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RA2120-1FE24-0BB4>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RA2120-1FE24-0BB4>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[https://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RA2120-1FE24-0BB4&lang=en](https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RA2120-1FE24-0BB4&lang=en)

Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RA2120-1FE24-0BB4>

Characteristic curves

[https://curves.simaris.siemens.com/curves/<mmp\\_prod\\_noCOMP="](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)





last modified:

4/24/2026 