



Connection terminal Cable entry left 690V AC, 1000 V DC, 80 A IP20

| Model | |
|--|--------------------------|
| product brand name | SETRON |
| product designation | Busbar systems |
| design of the product | Accessories |
| Supply voltage | |
| operating voltage at AC rated value | 690 V |
| Connections | |
| tightening torque | |
| • minimum | 1 N·m |
| • maximum | 2 N·m |
| type of connectable conductor cross-sections for copper conductor stranded | 6 - 25 mm ² |
| Mechanical Design | |
| height | 17.7 mm |
| width | 17.5 mm |
| depth | 13 mm |
| length | 26.5 mm |
| Net Weight | 13 g |
| Approvals Certificates | |
| Environment | General Product Approval |

[Environmental Confirmations](#)

[Environmental Confirmations](#)

[Miscellaneous](#)



[Confirmation](#)



| | |
|--------------------------|-------|
| General Product Approval | other |
|--------------------------|-------|



[Confirmation](#)

Further information

- Information on the packaging <https://support.industry.siemens.com/cs/ww/en/view/109813875>
- Information for data generation and storage <https://support.industry.siemens.com/cs/ww/en/view/109995012>
- Information- and Downloadcenter (Catalogs, Brochures,...) <https://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3768-4>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5ST3768-4>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3768-4

CAX-Online-Generator

<https://www.siemens.com/cax>

Tender specifications

<https://www.siemens.com/specifications>

Characteristic curves

[https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP="HAUPT"></mmp_prod_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)

last modified:

4/11/2025 

