



SITOP PSU8200/3AC/48VDC/10A

SITOP PSU8200 48 V/10 A stabilized power supply input: 400-500 V 3 AC output: 48 V DC/10 A

General information	
Technical Product Detail Page	<a href="https://i.siemens.com/1P6EP3446-8SB00-0AY0">https://i.siemens.com/1P6EP3446-8SB00-0AY0</a>
input	
type of the power supply network	3-phase AC
supply voltage at AC	
• minimum rated value	400 V
• maximum rated value	500 V
• initial value	320 V
• full-scale value	575 V
wide range input	Yes
buffering time for rated value of the output current in the event of power failure minimum	15 ms
operating condition of the mains buffering	at $V_{in} = 400\text{ V}$
line frequency	50/60 Hz
line frequency	47 ... 63 Hz
input current	
• at rated input voltage 400 V	1.2 A
• at rated input voltage 500 V	1 A
current limitation of inrush current at 25 °C maximum	16 A
I <sup>2</sup> t value maximum	0.8 A <sup>2</sup> ·s
fuse protection type	none
fuse protection type in the feeder	Required: 3-pole connected miniature circuit breaker 6 ... 16 A characteristic C or circuit breaker 3RV2011-1DA10 (setting 3 A) or 3RV2711-1DD10 (UL 489)
output	
voltage curve at output	Controlled, isolated DC voltage
output voltage at DC rated value	48 V
output voltage	
• at output 1 at DC rated value	48 V
output voltage adjustable	Yes; via potentiometer
adjustable output voltage	42 ... 56 V; max. 480 W
relative overall tolerance of the voltage	3 %
relative control precision of the output voltage	
• on slow fluctuation of input voltage	0.1 %
• on slow fluctuation of ohm loading	0.2 %
residual ripple	
• maximum	100 mV
voltage peak	
• maximum	200 mV
display version for normal operation	Green LED for 48 V OK

type of signal at output	Relay contact (NO contact, rating 60 V DC/ 0.3 A) for 48 V OK
behavior of the output voltage when switching on	No overshoot of Vout (soft start)
response delay maximum	2.5 s
voltage increase time of the output voltage <ul style="list-style-type: none"> <li>• maximum</li> </ul>	500 ms
output current <ul style="list-style-type: none"> <li>• rated value</li> <li>• rated range</li> </ul>	10 A 0 ... 10 A; +60 ... +70 °C: Derating 2%/K
supplied active power typical	480 W
short-term overload current <ul style="list-style-type: none"> <li>• at short-circuit during operation typical</li> </ul>	30 A
duration of overloading capability for excess current <ul style="list-style-type: none"> <li>• at short-circuit during operation</li> </ul>	25 ms
constant overload current <ul style="list-style-type: none"> <li>• on short-circuiting during the start-up typical</li> </ul>	11 A
bridging of equipment	Yes; switchable characteristic
number of parallel-switched equipment resources for increasing the power	2
<b>efficiency</b>	
efficiency in percent	94 %
power loss [W] <ul style="list-style-type: none"> <li>• at rated output voltage for rated value of the output current typical</li> </ul>	31 W
<b>closed-loop control</b>	
relative control precision of the output voltage with rapid fluctuation of the input voltage by +/- 15% typical	0.1 %
relative control precision of the output voltage load step of resistive load 50/100/50 % typical	1 %
setting time <ul style="list-style-type: none"> <li>• load step 50 to 100% typical</li> <li>• load step 100 to 50% typical</li> </ul>	0.2 ms 0.2 ms
relative control precision of the output voltage at load step of resistive load 10/90/10 % typical	2 %
setting time <ul style="list-style-type: none"> <li>• load step 10 to 90% typical</li> <li>• load step 90 to 10% typical</li> <li>• maximum</li> </ul>	0.2 ms 0.2 ms 10 ms
<b>protection and monitoring</b>	
design of the overvoltage protection	< 60 V
property of the output short-circuit proof	Yes
design of short-circuit protection <ul style="list-style-type: none"> <li>• typical</li> </ul>	Alternatively, constant current characteristic approx. 11 A or latching shutdown 11 A
overcurrent overload capability <ul style="list-style-type: none"> <li>• in normal operation</li> </ul>	overload capability 150 % Iout rated up to 5 s/min
enduring short circuit current RMS value <ul style="list-style-type: none"> <li>• typical</li> </ul>	11 A
display version for overload and short circuit	LED yellow for "overload", LED red for "latching shutdown"
<b>safety</b>	
galvanic isolation between input and output	Yes
galvanic isolation	Output voltage: SELV, ES1 (IEC 62368-1), DVC As (IEC 61204-7)
operating resource protection class	Class I
leakage current <ul style="list-style-type: none"> <li>• maximum</li> <li>• typical</li> </ul>	3.5 mA 0.9 mA
protection class IP	IP20
<b>EMC</b>	
standard <ul style="list-style-type: none"> <li>• for emitted interference</li> <li>• for mains harmonics limitation</li> <li>• for interference immunity</li> </ul>	EN 55022 Class B EN 61000-3-2 EN 61000-6-2

**standards, specifications, approvals**

certificate of suitability	
<ul style="list-style-type: none"> <li>• CE marking</li> <li>• UL approval</li> <li>• EAC approval</li> <li>• Regulatory Compliance Mark (RCM)</li> <li>• NEC Class 2</li> <li>• SEMI F47</li> </ul>	<ul style="list-style-type: none"> <li>Yes</li> <li>Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259</li> <li>Yes</li> <li>Yes</li> <li>No</li> <li>Yes</li> </ul>
type of certification	
<ul style="list-style-type: none"> <li>• CB-certificate</li> </ul>	Yes

**standards, specifications, approvals hazardous environments**

certificate of suitability	
<ul style="list-style-type: none"> <li>• IECEx</li> <li>• ATEX</li> <li>• ULhazloc approval</li> <li>• FM registration</li> </ul>	<ul style="list-style-type: none"> <li>No</li> <li>No</li> <li>No</li> <li>No</li> </ul>

**standards, specifications, approvals marine classification**

shipbuilding approval	Yes
Marine classification association	
<ul style="list-style-type: none"> <li>• American Bureau of Shipping Europe Ltd. (ABS)</li> <li>• French marine classification society (BV)</li> <li>• Det Norske Veritas (DNV)</li> <li>• Lloyds Register of Shipping (LRS)</li> </ul>	<ul style="list-style-type: none"> <li>Yes</li> <li>No</li> <li>Yes</li> <li>No</li> </ul>

**standards, specifications, approvals Environmental Product Declaration**

Environmental Product Declaration	Yes
global warming potential [CO <sub>2</sub> eq]	
<ul style="list-style-type: none"> <li>• total</li> <li>• during manufacturing</li> <li>• during operation</li> <li>• after end of life</li> </ul>	<ul style="list-style-type: none"> <li>814.2 kg</li> <li>28.7 kg</li> <li>785 kg</li> <li>0.24 kg</li> </ul>

**ambient conditions**

ambient temperature	
<ul style="list-style-type: none"> <li>• during operation</li> <li>• during transport</li> <li>• during storage</li> </ul>	<ul style="list-style-type: none"> <li>-25 ... +70 °C; with natural convection</li> <li>-40 ... +85 °C</li> <li>-40 ... +85 °C</li> </ul>
environmental category according to IEC 60721	Climate class 3K3, 5 ... 95% no condensation

**connection method**

type of electrical connection	screw terminal
<ul style="list-style-type: none"> <li>• at input</li> <li>• at output</li> <li>• for auxiliary contacts</li> </ul>	<ul style="list-style-type: none"> <li>L1, L2, L3, PE: 1 screw terminal each for 0.2 ... 4 mm<sup>2</sup> single-core/finely stranded</li> <li>+, -: 2 screw terminals each for 0.2 ... 4 mm<sup>2</sup></li> <li>13, 14 (alarm signal): 1 screw terminal each for 0.14 ... 1.5 mm<sup>2</sup>; 15, 16 (Remote): 1 screw terminal each for 0.14 ... 1.5 mm<sup>2</sup></li> </ul>

**mechanical data**

width × height × depth of the enclosure	70 × 125 × 125 mm
installation width × mounting height	70 mm × 225 mm
required spacing	
<ul style="list-style-type: none"> <li>• top</li> <li>• bottom</li> <li>• left</li> <li>• right</li> </ul>	<ul style="list-style-type: none"> <li>50 mm</li> <li>50 mm</li> <li>0 mm</li> <li>0 mm</li> </ul>
fastening method	Snaps onto DIN rail EN 60715 35x7.5/15
<ul style="list-style-type: none"> <li>• DIN-rail mounting</li> <li>• S7 rail mounting</li> <li>• wall mounting</li> </ul>	<ul style="list-style-type: none"> <li>Yes</li> <li>No</li> <li>No</li> </ul>
housing can be lined up	Yes
net weight	1.2 kg

**accessories**

mechanical accessories	Device identification label 20 mm × 7 mm, TI-grey 3RT2900-1SB20
------------------------	---

**further information internet links**

internet link	<ul style="list-style-type: none"> <li>• to website: Industry Mall <a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a></li> <li>• to web page: selection aid TIA Selection Tool <a href="https://www.siemens.com/tstcloud">https://www.siemens.com/tstcloud</a></li> <li>• to web page: power supplies <a href="https://siemens.com/sitop">https://siemens.com/sitop</a></li> <li>• to website: CAx-Download-Manager <a href="https://siemens.com/cax">https://siemens.com/cax</a></li> <li>• to website: Industry Online Support <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a></li> </ul>
identification link	Yes; acc. to IEC 61406-1:2022

**additional information**

other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)
-------------------	---

**security information**

security information	<p>Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit <a href="http://www.siemens.com/cybersecurity-industry">www.siemens.com/cybersecurity-industry</a>. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <a href="https://www.siemens.com/cert">https://www.siemens.com/cert</a>. (V4.7)</p>
----------------------	---

**Classifications**

	Version	Classification
eClass	14	27-04-07-01
eClass	12	27-04-07-01
eClass	9.1	27-04-07-01
eClass	9	27-04-07-01
eClass	8	27-04-90-02
eClass	7.1	27-04-90-02
eClass	6	27-04-90-02
ETIM	10	EC002540
ETIM	9	EC002540
ETIM	8	EC002540
ETIM	7	EC002540
IDEA	4	4130
UNSPSC	15	39-12-10-04

**Approvals Certificates**

<b>Environmental Product Declaration</b>	
• global warming potential [CO2 eq] / during manufacturing	28.7 kg
• global warming potential [CO2 eq] / during operation	785 kg
• global warming potential [CO2 eq] / after end of life	0.24 kg
• global warming potential [CO2 eq] / total	814.2 kg

<b>Environment</b>	<b>General Product Approval</b>
--------------------	---------------------------------



[Manufacturer Declaration](#)

[Declaration of Conformity](#)



<b>General Product Approval</b>	<b>Maritime application</b>
---------------------------------	-----------------------------

[China RoHS](#)



---

last modified:

5/5/2026