


Phase Control Thyristor

multicompPRO

**RoHS
Compliant**



Outline type code: F

Features

- Double Side Cooling
- High Surge Capability

Applications

- High Power Drives
- High Voltage Power Supplies
- Static Switches

Key Parameters

Part Number	Repetitive Peak Voltages V_{DRM} and V_{RRM} V	$I_{T(AV)}$	I_{TSM}	dV/dt^*	dI/dt	Conditions
MPPCT1560F260	2600	1560 A	24000 A	1000 V/ μ s	200 A/ μ s	$T_{vj} = -40^{\circ}\text{C}$ to 125°C , $I_{DRM} = I_{RRM} = 150\text{mA}$, V_{DRM} , V_{RRM} $t_p = 10\text{ms}$, V_{DSM} & $V_{RSM} =$ V_{DRM} & $V_{RRM} + 100\text{V}$ respectively

Current Ratings

$T_{case} = 60^{\circ}\text{C}$ unless stated otherwise

Symbol	Parameter	Test Conditions	Max.	Units
$I_{T(AV)}$	Mean on-state current	Half wave resistive load	1560	A
$I_{T(RMS)}$	RMS value	-	2450	
I_T	Continuous (direct) on-state current	-	2210	

Surge Ratings

Symbol	Parameter	Test Conditions	Max.	Units
I_{TSM}	Surge (non-repetitive) on-state current	10ms half sine, $T_{case} = 125^{\circ}\text{C}$ $V_R = 0$	24	kA
I^2t	I^2t for fusing		2.88	MA^2s

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro

multicompPRO

Thermal and Mechanical Ratings

Symbol	Parameter	Test Conditions		Min.	Max.	Units
R _{th(j-c)}	Thermal resistance – junction to case	Double side cooled	DC	-	0.02	°C/W
R _{th(c-h)}	Thermal resistance – case to heatsink				0.005	
T _{vj}	Virtual junction temperature	Blocking V _{DRM} / V _{RRM}				125
T _{stg}	Storage temperature range			-40	140	
F _m	Clamping force			12	26	kN

Dynamic Characteristics

Symbol	Parameter	Test Conditions		Min.	Max.	Units
I_{RRM}/I_{DRM}	Peak reverse and off-state current	At V_{RRM}/V_{DRM} , $T_{case} = 125^{\circ}C$		-	150	mA
dV/dt	Max. linear rate of rise of off-state voltage	To 67% V_{DRM} , $T_j = 125^{\circ}C$, gate open		1000	-	V/ μs
di/dt	Rate of rise of on-state current	From 67% V_{DRM} to 2000A Gate source 30V, 10 Ω , $t_r < 0.5\mu s$, $T_j = 125^{\circ}C$	Repetitive 50Hz	-	200	A/ μs
			Non-repetitive		1000	
V_T	On-state voltage	$I_T = 1500A$, $T_{case} = 125^{\circ}C$			1.3	V
$V_{T(TO)}$	Threshold voltage – Low level	$T_{case} = 125^{\circ}C$			0.89	
r_T	On-state slope resistance – Low level	$T_{case} = 125^{\circ}C$			0.27	m Ω
t_{gd}	Delay time	$V_D = 67\% V_{DRM}$, gate source 30V, 10 Ω $t_r = 0.5\mu s$, $T_j = 25^{\circ}C$			3	μs
t_q	Turn-off time	$T_j = 125^{\circ}C$, $V_R = 100V$, $di/dt = 10A/\mu s$, $dV_{DR}/dt = 20V/\mu s$ linear to 67% V_{DRM}			300	
Q_S	Stored charge	$I_T = 2000A$, $t_p = 1000\mu s$, $T_j = 125^{\circ}C$, $di/dt = 10A/\mu s$,			3200	μC
I_{RR}	Reverse recovery current				160	A
I_L	Latching current	$T_j = 25^{\circ}C$,			1	
I_H	Holding current	$T_j = 25^{\circ}C$,			200	mA

Gate Trigger Characteristics and Ratings

Symbol	Parameter	Test Conditions	Max.	Units
V_{GT}	Gate trigger voltage	$V_{DRM} = 5V$, $T_{case} = 25^{\circ}C$	3	V
V_{GD}	Gate non-trigger voltage	At 40% V_{DRM} , $T_{case} = 125^{\circ}C$	0.3	
I_{GT}	Gate trigger current	$V_{DRM} = 5V$, $T_{case} = 25^{\circ}C$	300	mA
I_{GD}	Gate non-trigger current	At 40% V_{DRM} , $T_{case} = 125^{\circ}C$	20	

Performance Curves




Fig.2 Maximum & minimum on-state characteristics




Fig.3 Maximum (limit) transient thermal impedance – junction to case (°C/W)




Fig.4 On-state power dissipation – sine wave




Fig.5 Maximum permissible case temperature, double side cooled – sine wave




Fig.6 Maximum permissible case temperature, double side cooled – rectangular wave




Fig.7 On-state power dissipation – rectangular wave




Fig.8 Multi-cycle surge current




Fig.9 Single-cycle I^2t




Fig.10 Stored charge vs di/dt




Fig.11 Reverse recovery current vs di/dt




Fig.12 Gate characteristics





Fig.13 Gate characteristics

Phase Control Thyristor

multicompPRO



Part Number Table

Description	Part Number
Phase Control Thyristor Module, 2600V, 1560A, F Case Code	MPPCT1560F260

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro

multicompPRO