

Datasheet

IEC Glassfibre Exposed Welded Tip Thermocouples, with & without Miniature Thermocouple Plug



- Thermocouple types K
- Fast response, welded exposed junction
- Various lengths of glassfibre insulated flat pair cable
- Good temperature resistance (not suitable in fluids)
- 1/0.508mm conductors
- Bare wire or Re-Wireable miniature flat pin plug
- Temperature range -60°C to +350°C (short periods up to 400°C)
- Tolerance to IEC 584 Class 2
- Colour code to IEC 584-3
- Ideal for test & development applications

T/C Type	Conductors	Length	Termination	+Positive tail wire	-Negative tail wire	Order code
'K'	1/0.508mm	1 metres	Bare wire	Green	White	XF-1533-FAR
'K'	1/0.508mm	2 metres	Bare wire	Green	White	XF-1213-FAR
'K'	1/0.508mm	5 metres	Bare wire	Green	White	XF-1214-FAR
'K'	1/0.508mm	10 metres	Bare wire	Green	White	XF-1222-FAR
'K'	1/0.508mm	1 metres	Mini plug	Green	White	XF-1223-FAR
'K'	1/0.508mm	2 metres	Mini plug	Green	White	XF-1512-FAR
'K'	1/0.508mm	5 metres	Mini plug	Green	White	XF-1210-FAR
'K'	1/0.508mm	10 metres	Mini plug	Green	White	XF-1224-FAR