


**SAK Series**  
**ASK 1/15**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Product image****Klippon® Connect with clamping yoke Technology**

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

**General ordering data**

|            |                                                                                                 |
|------------|-------------------------------------------------------------------------------------------------|
| Type       | ASK 1/15                                                                                        |
| Order No.  | <a href="#">0376860000</a>                                                                      |
| Version    | SAK Series, Fuse terminal, Rated cross-section: 4 mm², Screw connection, beige, Direct mounting |
| GTIN (EAN) | 4008190141202                                                                                   |
| Qty.       | 100 pc(s).                                                                                      |

**SAK Series**  
**ASK 1/15**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**
**Dimensions and weights**

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Width      | 8 mm    | Width (inches)  | 0.315 inch |
| Height     | 58 mm   | Height (inches) | 2.283 inch |
| Depth      | 34 mm   | Depth (inches)  | 1.339 inch |
| Net weight | 11.67 g |                 |            |

**Temperatures**

|                                  |                |                                  |        |
|----------------------------------|----------------|----------------------------------|--------|
| Storage temperature, max.        | 55 °C          | Storage temperature, min.        | -25 °C |
| Storage temperature              | -25 °C...55 °C | Continuous operating temp., min. | -50 °C |
| Continuous operating temp., max. | 100 °C         |                                  |        |

**Material data**

|                           |       |        |       |
|---------------------------|-------|--------|-------|
| Material                  | PA 66 | Colour | beige |
| UL 94 flammability rating | V-2   |        |       |

**System specifications**

|                                     |                                                            |                               |     |
|-------------------------------------|------------------------------------------------------------|-------------------------------|-----|
| Version                             | Screw connection, Fuse isolator, One end without connector | End cover plate required      | Yes |
| Number of potentials                | 1                                                          | Number of levels              | 1   |
| Number of clamping points per level | 2                                                          | Number of potentials per tier | 1   |
| Levels cross-connected internally   | No                                                         | PE connection                 | No  |
| Rail                                | TS 15                                                      | N-function                    | No  |
| PE function                         | No                                                         | PEN function                  | No  |

**Additional technical data**

|                             |         |                     |                 |
|-----------------------------|---------|---------------------|-----------------|
| Explosion-tested version    | No      | Installation advice | Direct mounting |
| Number of similar terminals | 1       | Open sides          | right           |
| Type of mounting            | Snap-on |                     |                 |

**CSA rating data**

|                               |                |                               |        |
|-------------------------------|----------------|-------------------------------|--------|
| Certificate No. (CSA)         | 200039-2372908 | Current size B (CSA)          | 10 A   |
| Current size C (CSA)          | 10 A           | Current size D (CSA)          | 10 A   |
| Voltage size B (CSA)          | 300 V          | Voltage size C (CSA)          | 300 V  |
| Voltage size D (CSA)          | 300 V          | Wire cross section max. (CSA) | 12 AWG |
| Wire cross section min. (CSA) | 26 AWG         |                               |        |

**SAK Series**  
**ASK 1/15**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**
**Conductors for clamping (rated connection)**

|                                                                                         |                      |                                                                                         |                     |
|-----------------------------------------------------------------------------------------|----------------------|-----------------------------------------------------------------------------------------|---------------------|
| Blade size                                                                              | 0.6 x 3.5 mm         | Clamping range, max.                                                                    | 4 mm <sup>2</sup>   |
| Clamping range, min.                                                                    | 0.13 mm <sup>2</sup> | Clamping screw                                                                          | M 3                 |
| Connection cross-section, stranded, max.                                                | 4 mm <sup>2</sup>    | Connection cross-section, stranded, min.                                                | 1.5 mm <sup>2</sup> |
| Connection direction                                                                    | on side              | Gauge to IEC 60947-1                                                                    | A3                  |
| Number of connections                                                                   | 2                    | Stripping length                                                                        | 9 mm                |
| Tightening torque, max.                                                                 | 1 Nm                 | Tightening torque, min.                                                                 | 0.5 Nm              |
| Torque level with DMS electric screwdriver                                              | 2                    | Twin wire-end ferrules, max.                                                            | 1.5 mm <sup>2</sup> |
| Twin wire-end ferrules, min.                                                            | 0.5 mm <sup>2</sup>  | Type of connection                                                                      | Screw connection    |
| Wire connection cross section AWG, max.                                                 | AWG 12               | Wire connection cross section AWG, min.                                                 | AWG 26              |
| Wire connection cross section, finely stranded, max.                                    | 4 mm <sup>2</sup>    | Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, max. | 4 mm <sup>2</sup>   |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, min. | 0.5 mm <sup>2</sup>  | Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, max. | 4 mm <sup>2</sup>   |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, min. | 0.5 mm <sup>2</sup>  | Wire connection cross-section, finely stranded, min.                                    | 0.5 mm <sup>2</sup> |
| Wire connection cross-section, solid core, max.                                         | 4 mm <sup>2</sup>    | Wire connection cross-section, solid core, min.                                         | 0.5 mm <sup>2</sup> |

**Dimensions**

|              |       |
|--------------|-------|
| TS 15 offset | 26 mm |
|--------------|-------|

**Display element**

|                                     |       |                               |       |
|-------------------------------------|-------|-------------------------------|-------|
| Operating voltage for display, max. | 500 V | Type of voltage for indicator | AC/DC |
|-------------------------------------|-------|-------------------------------|-------|

**Fuse terminals**

|                                |              |                         |             |
|--------------------------------|--------------|-------------------------|-------------|
| Cartridge fuse                 | G-Si. 5 x 20 | Display                 | Without LED |
| Fuse holder (cartridge holder) | Pivoting     | Operating voltage, max. | 400 V       |
| Type of voltage for indicator  | AC/DC        |                         |             |

**Rating data**

|                                              |                   |                                             |        |
|----------------------------------------------|-------------------|---------------------------------------------|--------|
| Rated cross-section                          | 4 mm <sup>2</sup> | Rated voltage                               | 500 V  |
| Rated current                                | 6.3 A             | Current at maximum wires                    | 6.3 A  |
| Volume resistance according to IEC 60947-7-x | 1 mΩ              | Power loss in accordance with IEC 60947-7-x | 1.02 W |
| Rated impulse withstand voltage              | 6 kV              | Pollution severity                          | 3      |

**UL rating data**

|                                         |        |                                         |        |
|-----------------------------------------|--------|-----------------------------------------|--------|
| Certificate No. (UR)                    | E60693 | Conductor size Factory wiring max. (UR) | 12 AWG |
| Conductor size Factory wiring min. (UR) | 26 AWG | Conductor size Field wiring max. (UR)   | 12 AWG |
| Conductor size Field wiring min. (UR)   | 22 AWG | Current size C (UR)                     | 10 A   |
| Voltage size C (UR)                     | 300 V  |                                         |        |

**SAK Series**  
**ASK 1/15**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Technical data**
**Classifications**

|             |             |            |             |
|-------------|-------------|------------|-------------|
| ETIM 6.0    | EC000899    | ETIM 7.0   | EC000899    |
| eClass 9.0  | 27-14-11-16 | eClass 9.1 | 27-14-11-16 |
| eClass 10.0 | 27-14-11-16 | UNSPSC     | 30-21-18-11 |

**Approvals**

Approvals



ROHS Conform

**Downloads**

|                                             |                                                                                                                                                                                      |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">EAC certificate</a><br><a href="#">MARITREG Certificate</a><br><a href="#">DE_PT1373_20160418_025_ISSUE01.pdf</a><br><a href="#">Declaration of Conformity Terminals</a> |
| Engineering Data                            | <a href="#">EPLAN, WSCAD</a>                                                                                                                                                         |
| Engineering Data                            | <a href="#">STEP</a>                                                                                                                                                                 |
| User Documentation                          | <a href="#">StorageConditionsTerminalBlocks</a>                                                                                                                                      |

**Safety note**

 Safety notice [Safety Information](#)