


**SAK Series  
SAK 35/35**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Product image****Klippon® Connect with clamping yoke Technology**

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

**General ordering data**

|            |                                                                                                      |
|------------|------------------------------------------------------------------------------------------------------|
| Type       | SAK 35/35                                                                                            |
| Order No.  | <a href="#">0380760000</a>                                                                           |
| Version    | SAK Series, Feed-through terminal, Rated cross-section: 35 mm <sup>2</sup> , Screw connection, beige |
| GTIN (EAN) | 4008 190063962                                                                                       |
| Qty.       | 20 pc(s).                                                                                            |

**SAK Series**  
**SAK 35/35**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data****Dimensions and weights**

|        |         |                 |            |
|--------|---------|-----------------|------------|
| Width  | 18 mm   | Width (inches)  | 0.709 inch |
| Height | 58 mm   | Height (inches) | 2.283 inch |
| Depth  | 60 mm   | Depth (inches)  | 2.362 inch |
| Weight | 69.35 g | Net weight      | 52.15 g    |

**Temperatures**

|                                  |                                                                                                   |                                  |                |
|----------------------------------|---------------------------------------------------------------------------------------------------|----------------------------------|----------------|
| Operating temperature range      | For operating temperature range see EC Design Test Certificate / IEC Ex-Certificate of Conformity | Storage temperature, max.        | 55 °C          |
| Storage temperature, min.        | -25 °C                                                                                            | Storage temperature              | -25 °C...55 °C |
| Continuous operating temp., min. | -50 °C                                                                                            | Continuous operating temp., max. | 100 °C         |

**Material data**

|                           |       |        |                |
|---------------------------|-------|--------|----------------|
| Material                  | PA 66 | Colour | beige / yellow |
| UL 94 flammability rating | V-2   |        |                |

**Rating data IECEx/ATEX**

|                                |                                                                                                   |                                 |                    |
|--------------------------------|---------------------------------------------------------------------------------------------------|---------------------------------|--------------------|
| Certificate No. (ATEX)         | KEMA97ATEX1798U                                                                                   | Certificate No. (IECEX)         | IECEXKEM06.0014U   |
| Max. voltage (ATEX)            | 550 V                                                                                             | Current (ATEX)                  | 109 A              |
| Wire cross section max. (ATEX) | 35 mm <sup>2</sup>                                                                                | Max. voltage (IECEX)            | 550 V              |
| Current (IECEX)                | 109 A                                                                                             | Wire cross section max. (IECEX) | 35 mm <sup>2</sup> |
| Operating temperature range    | For operating temperature range see EC Design Test Certificate / IEC Ex-Certificate of Conformity | Marking EN 60079-7              | Ex eb II C Gb      |
| Ex 2014/34/EU label            | II 2 G D                                                                                          |                                 |                    |

**System specifications**

|                                     |                                                                             |                               |     |
|-------------------------------------|-----------------------------------------------------------------------------|-------------------------------|-----|
| Version                             | Screw connection, for screwable cross-connection, One end without connector | End cover plate required      | Yes |
| Number of potentials                | 1                                                                           | Number of levels              | 1   |
| Number of clamping points per level | 2                                                                           | Number of potentials per tier | 1   |
| Levels cross-connected internally   | No                                                                          | PE connection                 | No  |
| Rail                                | TS 35                                                                       | N-function                    | No  |
| PE function                         | No                                                                          | PEN function                  | No  |

**Additional technical data**

|                          |       |                             |         |
|--------------------------|-------|-----------------------------|---------|
| Explosion-tested version | Yes   | Number of similar terminals | 1       |
| Open sides               | right | Type of mounting            | Clamped |

**CSA rating data**

|                               |                |                               |       |
|-------------------------------|----------------|-------------------------------|-------|
| Certificate No. (CSA)         | 154685-1501714 | Current size C (CSA)          | 145 A |
| Voltage size C (CSA)          | 600 V          | Wire cross section max. (CSA) | 2 AWG |
| Wire cross section min. (CSA) | 12 AWG         |                               |       |

**SAK Series**  
**SAK 35/35**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**
**Conductors for clamping (additional connection)**

Conductor cross-section, flexible plus plastic collar DIN 46228/1, further connection, max. 35 mm<sup>2</sup>

**Conductors for clamping (rated connection)**

|                                                                                         |                     |                                                                                         |                     |
|-----------------------------------------------------------------------------------------|---------------------|-----------------------------------------------------------------------------------------|---------------------|
| Blade size                                                                              | 6.5 x 1.2 mm        | Clamping range, max.                                                                    | 50 mm <sup>2</sup>  |
| Clamping range, min.                                                                    | 2.5 mm <sup>2</sup> | Clamping screw                                                                          | M 6                 |
| Connection cross-section, stranded, max.                                                | 50 mm <sup>2</sup>  | Connection cross-section, stranded, min.                                                | 4 mm <sup>2</sup>   |
| Connection direction                                                                    | on side             | Gauge to IEC 60947-1                                                                    | B8                  |
| Number of connections                                                                   | 2                   | Stripping length                                                                        | 18 mm               |
| Tightening torque, max.                                                                 | 5 Nm                | Tightening torque, min.                                                                 | 2.5 Nm              |
| Twin wire-end ferrules, max.                                                            | 16 mm <sup>2</sup>  | Twin wire-end ferrules, min.                                                            | 1.5 mm <sup>2</sup> |
| Type of connection                                                                      | Screw connection    | Wire connection cross section AWG, max.                                                 | AWG 2               |
| Wire connection cross section AWG, min.                                                 | AWG 12              | Wire connection cross section, finely stranded, max.                                    | 35 mm <sup>2</sup>  |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, max. | 35 mm <sup>2</sup>  | Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, min. | 2.5 mm <sup>2</sup> |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, max. | 35 mm <sup>2</sup>  | Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, min. | 2.5 mm <sup>2</sup> |
| Wire connection cross-section, finely stranded, min.                                    | 2.5 mm <sup>2</sup> | Wire connection cross-section, solid core, max.                                         | 16 mm <sup>2</sup>  |
| Wire connection cross-section, solid core, min.                                         | 2.5 mm <sup>2</sup> |                                                                                         |                     |

**Rating data**

|                                             |                    |                                              |         |
|---------------------------------------------|--------------------|----------------------------------------------|---------|
| Rated cross-section                         | 35 mm <sup>2</sup> | Rated voltage                                | 800 V   |
| Rated current                               | 125 A              | Current at maximum wires                     | 150 A   |
| Standards                                   | IEC 60947-7-1      | Volume resistance according to IEC 60947-7-x | 0.26 mΩ |
| Power loss in accordance with IEC 60947-7-x | 4 W                | Rated impulse withstand voltage              | 8 kV    |
| Pollution severity                          | 3                  |                                              |         |

**UL rating data**

|                                         |        |                                         |       |
|-----------------------------------------|--------|-----------------------------------------|-------|
| Certificate No. (UR)                    | E60693 | Conductor size Factory wiring max. (UR) | 2 AWG |
| Conductor size Factory wiring min. (UR) | 6 AWG  | Conductor size Field wiring max. (UR)   | 2 AWG |
| Conductor size Field wiring min. (UR)   | 6 AWG  | Current size C (UR)                     | 105 A |
| Voltage size C (UR)                     | 600 V  |                                         |       |

**Classifications**

|             |             |            |             |
|-------------|-------------|------------|-------------|
| ETIM 6.0    | EC000897    | ETIM 7.0   | EC000897    |
| eClass 9.0  | 27-14-11-20 | eClass 9.1 | 27-14-11-20 |
| eClass 10.0 | 27-14-11-20 | UNSPSC     | 30-21-18-11 |

## SAK Series SAK 35/35

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

## Technical data

### Approvals

Approvals



ROHS Conform

### Downloads

|                                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|---------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">Attestation Of Conformity</a><br><a href="#">ATEX Certificate</a><br><a href="#">IECEx Certificate</a><br><a href="#">CB Certificate</a><br><a href="#">CB Test Certificate</a><br><a href="#">EAC certificate</a><br><a href="#">DNVGL certificate</a><br><a href="#">Lloyds Register Certificate</a><br><a href="#">MARITREG Certificate</a><br><a href="#">Declaration of Conformity</a><br><a href="#">Declaration of Conformity</a> |
| Engineering Data                            | <a href="#">EPLAN, WSCAD</a>                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Engineering Data                            | <a href="#">STEP</a>                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| User Documentation                          | <a href="#">Cross Connection Guide</a><br><a href="#">StorageConditionsTerminalBlocks</a>                                                                                                                                                                                                                                                                                                                                                            |

### Safety note

Safety notice [Safety Information](#)

**SAK Series**  
**SAK 35/35**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Accessories****Plus**

The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

**General ordering data**

|            |                            |                                                           |
|------------|----------------------------|-----------------------------------------------------------|
| Type       | DEK 5/8 PLUS MC NE WS      | Version                                                   |
| Order No.  | <a href="#">1046350000</a> | Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00 |
| GTIN (EAN) | 4032248782055              | Weidmueller, white                                        |
| Qty.       | 800 pc(s).                 |                                                           |

**SAK Series**  
**SAK 35/35**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Accessories****DEK 5/6****WS/ DEK**

MultiMark DEK/WS connector markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wear-resistant labelling. A print resolution of 300 dpi also produces a very legible script.

**Your benefits with MultiMark**

- Firm hold and durable printing
- Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- Large label field for optimal legibility
- High flexibility thanks to manufacturer independence

**General ordering data**

|            |                            |                                                        |
|------------|----------------------------|--------------------------------------------------------|
| Type       | DEK 5/6 MM WS              | Version                                                |
| Order No.  | <a href="#">2007120000</a> | Dekafix, Terminal marker, 5 x 6 mm, Weidmueller, white |
| GTIN (EAN) | 4050118392104              |                                                        |
| Qty.       | 600 pc(s).                 |                                                        |

## SAK Series

### SAK 35/35

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Accessories

### Blank



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

### General ordering data

|            |                            |                                                           |
|------------|----------------------------|-----------------------------------------------------------|
| Type       | DEK 5/5 MC NE WS           | Version                                                   |
| Order No.  | <a href="#">1609801044</a> | Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00 |
| GTIN (EAN) | 4008190397111              | Weidmueller, white                                        |
| Qty.       | 1,000 pc(s).               |                                                           |

### Connection sleeves



VH 12/4.9/3.3 024900

### Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

### General ordering data

|            |                            |                                                                              |
|------------|----------------------------|------------------------------------------------------------------------------|
| Type       | VH 24.5/8/5 SAK35          | Version                                                                      |
| Order No.  | <a href="#">0298700000</a> | SAK Series, Connecting sleeve, for cross-connection link, Number of poles: 1 |
| GTIN (EAN) | 4008190070809              |                                                                              |
| Qty.       | 50 pc(s).                  |                                                                              |


|            |                            |                                                                            |
|------------|----------------------------|----------------------------------------------------------------------------|
| Type       | VH 17/8/5 SAK35            | Version                                                                    |
| Order No.  | <a href="#">0267000000</a> | SAK Series, Connecting sleeve, for cross-connection link, Number of poles: |
| GTIN (EAN) | 4008190146986              |                                                                            |
| Qty.       | 50 pc(s).                  |                                                                            |

## SAK Series SAK 35/35

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

## Accessories

### Custom printing



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.


- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

### General ordering data

|            |                            |                                                           |
|------------|----------------------------|-----------------------------------------------------------|
| Type       | DEK 5/6 MC SDR             | Version                                                   |
| Order No.  | <a href="#">1609830000</a> | Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00 |
| GTIN (EAN) | 4008190456603              | Weidmueller, To customer specification                    |
| Qty.       | 200 pc(s).                 |                                                           |

### Custom printing



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

### General ordering data

|            |                            |                                                           |
|------------|----------------------------|-----------------------------------------------------------|
| Type       | DEK 5/5 MC SDR             | Version                                                   |
| Order No.  | <a href="#">1609810000</a> | Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00 |
| GTIN (EAN) | 4008190456597              | Weidmueller, To customer specification                    |
| Qty.       | 200 pc(s).                 |                                                           |

## SAK Series SAK 35/35

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Accessories

### Custom printing



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

### General ordering data

|            |                            |                                                           |
|------------|----------------------------|-----------------------------------------------------------|
| Type       | DEK 5/8 MC SDR             | Version                                                   |
| Order No.  | <a href="#">1856750000</a> | Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00 |
| GTIN (EAN) | 4032248400867              | Weidmueller, To customer specification                    |
| Qty.       | 160 pc(s).                 |                                                           |
| Type       | DEK 5/8 PLUS MC SDR        | Version                                                   |
| Order No.  | <a href="#">1046370000</a> | Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00 |
| GTIN (EAN) | 4032248782079              | Weidmueller, To customer specification                    |
| Qty.       | 160 pc(s).                 |                                                           |

## SAK Series

### SAK 35/35

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Accessories

### DEK 5/8



#### WS/ DEK

MultiMark DEK/WS connector markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wear-resistant labelling. A print resolution of 300 dpi also produces a very legible script.

#### Your benefits with MultiMark

- Firm hold and durable printing
- Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- Large label field for optimal legibility
- High flexibility thanks to manufacturer independence

#### General ordering data

|            |                            |                                                        |
|------------|----------------------------|--------------------------------------------------------|
| Type       | DEK 5/8 MM WS              | Version                                                |
| Order No.  | <a href="#">2007130000</a> | Dekafix, Terminal marker, 5 x 8 mm, Weidmueller, white |
| GTIN (EAN) | 4050118392012              |                                                        |
| Qty.       | 500 pc(s).                 |                                                        |

### Screwing



#### Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

#### General ordering data

|            |                            |                                                        |
|------------|----------------------------|--------------------------------------------------------|
| Type       | BFSC M4X35                 | Version                                                |
| Order No.  | <a href="#">0298900000</a> | Accessories, Mounting screw, for cross-connection link |
| GTIN (EAN) | 4008190090487              |                                                        |
| Qty.       | 50 pc(s).                  |                                                        |
| Type       | BFSC M4X30                 | Version                                                |
| Order No.  | <a href="#">0267100000</a> | Accessories, Mounting screw, for cross-connection link |
| GTIN (EAN) | 4008190187897              |                                                        |
| Qty.       | 50 pc(s).                  |                                                        |


## SAK Series

### SAK 35/35

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Accessories

### Blank



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.


- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

### General ordering data

|            |                            |                                                           |
|------------|----------------------------|-----------------------------------------------------------|
| Type       | DEK 5/6 MC NE WS           | Version                                                   |
| Order No.  | <a href="#">1609820000</a> | Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00 |
| GTIN (EAN) | 4008190203436              | Weidmueller, white                                        |
| Qty.       | 1,000 pc(s).               |                                                           |

### Partition plates



### Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

### General ordering data

|            |                            |                                                              |
|------------|----------------------------|--------------------------------------------------------------|
| Type       | TW SAK35                   | Version                                                      |
| Order No.  | <a href="#">0304360000</a> | SAK Series, Separation plate, 1.5 mm, beige, Direct mounting |
| GTIN (EAN) | 4008190038885              |                                                              |
| Qty.       | 20 pc(s).                  |                                                              |

## SAK Series

### SAK 35/35

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Accessories

### Test plug



#### Current and voltage transformer wiring

Our test disconnect terminal blocks featuring spring and screw connection technology allow you to create all the important converter circuits for measuring current, voltage and power in a safe and sophisticated way.

#### General ordering data

|            |                            |                        |
|------------|----------------------------|------------------------|
| Type       | PS 4 F.STB 4               | Version                |
| Order No.  | <a href="#">0299600000</a> | Accessories, Test plug |
| GTIN (EAN) | 4008190074043              |                        |
| Qty.       | 20 pc(s).                  |                        |

### QL / SAK 35



#### Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

#### General ordering data

|            |                            |                                                                   |
|------------|----------------------------|-------------------------------------------------------------------|
| Type       | QL 4 SAK35                 | Version                                                           |
| Order No.  | <a href="#">0123800000</a> | SAK Series, Cross-connector, for cross-connection link, Number of |
| GTIN (EAN) | 4008190165390              | poles: 4                                                          |
| Qty.       | 20 pc(s).                  |                                                                   |
| Type       | QL 10 SAK35                | Version                                                           |
| Order No.  | <a href="#">0338600000</a> | SAK Series, Cross-connector, for cross-connection link, Number of |
| GTIN (EAN) | 4008190106133              | poles: 10                                                         |
| Qty.       | 20 pc(s).                  |                                                                   |
| Type       | QL 3 SAK35                 | Version                                                           |
| Order No.  | <a href="#">0123700000</a> | SAK Series, Cross-connector, for cross-connection link, Number of |
| GTIN (EAN) | 4008190182526              | poles: 3                                                          |
| Qty.       | 20 pc(s).                  |                                                                   |
| Type       | QL 2 SAK35                 | Version                                                           |
| Order No.  | <a href="#">0123600000</a> | SAK Series, Cross-connector, for cross-connection link, Number of |
| GTIN (EAN) | 4008190092566              | poles: 2                                                          |
| Qty.       | 20 pc(s).                  |                                                                   |

## SAK Series

### SAK 35/35

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Accessories

### End plates



#### Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

#### General ordering data

|            |                            |                                      |
|------------|----------------------------|--------------------------------------|
| Type       | AP SAK35/TW SAK16          | Version                              |
| Order No.  | <a href="#">0303660000</a> | SAK Series, End plate, 1.5 mm, beige |
| GTIN (EAN) | 4008190110765              |                                      |
| Qty.       | 10 pc(s).                  |                                      |
| Type       | AP SAK35/TW SAK16 BL       | Version                              |
| Order No.  | <a href="#">0303680000</a> | SAK Series, End plate, 1.5 mm, blue  |
| GTIN (EAN) | 4008190025199              |                                      |
| Qty.       | 10 pc(s).                  |                                      |

### Non-insulated sockets



#### Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

#### General ordering data

|            |                            |                    |
|------------|----------------------------|--------------------|
| Type       | STB 16/D7/4/M4 SAK35       | Version            |
| Order No.  | <a href="#">0140200000</a> | SAK Series, Socket |
| GTIN (EAN) | 4008190134884              |                    |
| Qty.       | 50 pc(s).                  |                    |

**SAK Series**  
**SAK 35/35**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Accessories**
**Blank**


The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

**General ordering data**

|            |                            |                                                           |
|------------|----------------------------|-----------------------------------------------------------|
| Type       | DEK 5/8 MC NE WS           | Version                                                   |
| Order No.  | <a href="#">1856740000</a> | Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00 |
| GTIN (EAN) | 4032248400850              | Weidmueller, white                                        |
| Qty.       | 800 pc(s).                 |                                                           |

**Covers**

**Klippon® Connect with clamping yoke Technology**

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

**General ordering data**

|            |                            |                                          |
|------------|----------------------------|------------------------------------------|
| Type       | AD 4 SAK35                 | Version                                  |
| Order No.  | <a href="#">0178700000</a> | SAK Series, cover plate, yellow, 71.6 mm |
| GTIN (EAN) | 4008190056414              |                                          |
| Qty.       | 50 pc(s).                  |                                          |
| Type       | AD 3 SAK35                 | Version                                  |
| Order No.  | <a href="#">0273400000</a> | SAK Series, cover plate, yellow, 48 mm   |
| GTIN (EAN) | 4008190106027              |                                          |
| Qty.       | 50 pc(s).                  |                                          |