


## Data sheet Product WLFT 412 100x200



Accessories for electronic components>Thermal interface material>Thermally conductive foil both sides adhesive suitable for blanks

### Features

|                              |                                            |
|------------------------------|--------------------------------------------|
| dimensions:                  | 100x200 mm                                 |
| version:                     | non insulating, double-sided adhesive      |
| material thickness:          | 0.23 mm                                    |
| material filling:            | Aluminiumgeflecht                          |
| glue layer:                  | acrylate (pressure sensitive) double-sided |
| colour:                      | grey                                       |
| thermal conductivity:        | 1.4 W/m·K                                  |
| specific thermal resistance: | 2 °C cm <sup>2</sup> /W                    |
| holding force (overlapping): | 0.93 MPa                                   |
| temperature range:           | -30°C... +125°C                            |
| dielectric strength:         | 5 kV (AC)                                  |
| class of inflammability:     | UL 94 V-0                                  |
| type of delivery:            | plate                                      |

**Fischer Elektronik GmbH & Co. KG**  
DEUTSCHLAND • GERMANY • ALLEMAGNE

Nottebohmstraße 28  
58511 Lüdenscheid

Telefon +49 2351 435-0  
Telefax +49 2351 45754

info@fischerelektronik.de  
www.fischerelektronik.de