




All rights strictly reserved. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietor. Property of FCI. Copyright FCI.

Tous droits strictement réservés. Reproduction ou communication à des tiers interdite sous quelque forme que ce soit sans autorisation écrite du propriétaire. Propriété de c FCI. Droits de reproduction FCI.

CODE	DIM "M" ±0.010 [0.25]	CONTACT TYPE
H	0.220 [5.59]	SIGNAL
R	0.270 [6.86]	SIGNAL
S	0.270 [6.86]	SIGNAL
T	0.270 [6.86]	SIGNAL
U	0.270 [6.86]	SIGNAL
PA	N/A [N/A]	POWER



mat'l code				NOTE 1		tolerances unless otherwise specified		CUSTOMER COPY		FCI		www.fciconnect.com	
litr	ecn no.	dr	date	linear		.XX±.01/0.X±0.3		projection		title	10P + 16S + 3ACP RIGHT ANGLE SOLDER HEADER	product family	PwrBlade
A	V12145	JRW	08/08/01			.XXX±.005/0.XX±0.13				size	dwg no	code	213
B	DG06-0008	JMG	01/09/06			.XXX±.0020/0.XXX±0.051				scale	1:1	sheet	1 OF 2
C	DG08-0308	WD	11/05/08	angles		0°±2°							
				dr	J. WITMER	08/08/01							
				enr	J. ALLISON	08/08/01							
				chr	J. ALLISON	08/08/01							
				appd	J. ALLISON	08/08/01							
sheet index	revision sheet	C	C	I	2								

Pro/E



cage code 22526

Tous droits strictement réservés. Reproduction ou communication à des tiers interdite sous quelque forme que ce soit sans autorisation écrite du propriétaire. Propriété de c FCI. Droits de reproduction FCI.



All rights strictly reserved. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietor. Property of FCI. Copyright FCI.

PRODUCT NUMBER
51939-001--
NOTE: 2




CONNECTOR NOTES:

1. HOUSING MATERIAL: UL 94 V-0 GLASS FILLED HIGH TEMP THERMOPLASTIC
POWER CONTACT MATERIAL: COPPER ALLOY
SIGNAL CONTACT MATERIAL: COPPER ALLOY
2. SEE PRINT 10064183 FOR PLATING SPEC OF 51939 AND 51939LF RESPECTIVELY.
3. "MANUFACTURER" NAME, P/N, AND DATE CODE TO APPEAR ON THIS SURFACE
4. PRODUCT SPECIFICATION GS-12-149

PCB NOTES:

5. ALL DIMENSIONS ARE BASIC UNLESS OTHERWISE SPECIFIED.
6. ALL THROUGH HOLES ARE LOCATED WITH A TRUE POSITION OF 0.004 [0.10]
7. ALL HOLE DIAMETERS ARE FINISHED HOLE SIZE
8. $\varnothing 0.0453 \pm 0.0010$ [1.151 ±0.025] DRILLED HOLES PLATED WITH 0.0003 [0.008] MIN SnPb OVER 0.001 [0.03] TO 0.003 [0.08] Cu PLATING TO ACHIEVE A $\varnothing 0.040 \pm 0.003$ [1.02 ±0.07] HOLE.
9. AVOID HAVING EXPOSED CIRCUITRY IN THIS AREA.
10. A $\triangle$ SYMBOL WILL BE NEXT TO ANY DIMENSION, VIEW, OR NOTE WHICH HAS BEEN MODIFIED WITH THE CURRENT DRAWING REVISION.



RECOMMENDED PCB LAYOUT

NOTE 1				tolerances unless otherwise specified		CUSTOMER COPY		FCI	
ltr	ecn no.	dr	date	linear	$.XX \pm .01 / 0.X \pm 0.3$	projection		title	www.fciconnect.com
c				angles	$.XXX \pm .005 / 0.XX \pm 0.13$			10P + 16S + 3ACP	
					$.XXX \pm .0020 / 0.XXX \pm 0.051$			RIGHT ANGLE SOLDER HEADER	
				dr	J. WITMER 08/08/01	INCH/MM		product family	PwrBlade
				enr	J. ALLISON 08/08/01	scale		size	213
				chr	J. ALLISON 08/08/01	1:1		dwg no	51939
				appd	J. ALLISON 08/08/01			sheet	2
sheet index	revision sheet								

Pro/E

cage code 22526