


N- and P-Channel 100 V (D-S) MOSFET



RoHS
COMPLIANT
HALOGEN
FREE




FEATURES

- TrenchFET® power MOSFETs
- Thermally enhanced PowerPAK®
- 100 % R_g tested
- Material categorization:
for definitions of compliance please see
www.vishay.com/doc?99912

APPLICATIONS

- DC/DC converters
- Active clamp
- Brushless DC motors
- AC/DC inverter
- Motor drive switch



PRODUCT SUMMARY		
	N-CHANNEL	P-CHANNEL
V _{DS} (V)	100	-100
R _{DS(on)} (Ω) at V _{GS} = ± 10 V	0.167	0.251
R _{DS(on)} (Ω) at V _{GS} = ± 4.5 V	0.186	0.338
Q _g typ. (nC)	2.4	4.0
I _D (A) a, b	4	
Configuration	N- and p-pair	

ORDERING INFORMATION

Package	PowerPAK 1212-8
Lead (Pb)-free and halogen-free	SIS590DN-T1-GE3

ABSOLUTE MAXIMUM RATINGS (T_A = 25 °C, unless otherwise noted)

PARAMETER		SYMBOL	N-CHANNEL	P-CHANNEL	UNIT
Drain-source voltage		V _{DS}	100	-100	V
Gate-source voltage		V _{GS}	± 20		
Continuous drain current	T _C = 25 °C	I _D	4 ^g	4 ^g	A
	T _C = 70 °C		4 ^g	4 ^g	
	T _A = 25 °C		2.7 ^{a, b}	2.3 ^{a, b}	
	T _A = 70 °C		2.1	1.8	
Pulsed drain current (t = 100 μs)		I _{DM}	8	10	
Continuous source-drain diode current	T _C = 25 °C	I _S	14.9	19.3	
	T _C = 70 °C		9.5	12.3	
Single pulse avalanche current	L = 0.1 mH	I _{AS}	4	10	W
Single pulse avalanche energy		E _{AS}	0.8	5.0	
Maximum Power Dissipation	T _C = 25 °C	P _D	17.9	23.1	
	T _C = 70 °C		11.4	14.8	
	T _A = 25 °C		2.5 ^{a, b}	2.6 ^{a, b}	
	T _A = 70 °C		1.6	1.7	
Operating junction and storage temperature range		T _J , T _{stg}	-55 to +150		°C
Soldering recommendations (peak temperature) ^{d, e}			260		

THERMAL RESISTANCE RATINGS

PARAMETER		SYMBOL	N-CHANNEL		P-CHANNEL		UNIT
			TYP.	MAX.	TYP.	MAX.	
Maximum junction-to-ambient b, f	t ≤ 10 s	R _{thJA}	40	50	38	48	°C/W
Maximum junction-to-case (drain)	Steady state	R _{thJC}	5.6	7	4.3	5.4	

Notes

- Based on silicon capability only
- Surface mounted on 1" x 1" FR4 board
- t = 10 s
- See solder profile (www.vishay.com/doc?73257). The PowerPAK SO-8 is a leadless package. The end of the lead terminal is exposed copper (not plated) as a result of the singulation process in manufacturing. A solder fillet at the exposed copper tip cannot be guaranteed and is not required to ensure adequate bottom side solder interconnection
- Rework conditions: Manual soldering with a soldering iron is not recommended for leadless components
- Maximum under steady state conditions is 94 °C/W
- Package limited

**SPECIFICATIONS** ($T_J = 25\text{ }^{\circ}\text{C}$, unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITIONS		MIN.	TYP.	MAX	UNIT	
Static								
Drain-source breakdown voltage	V _{DS}	V _{GS} = 0 V, I _D = 250 μA	N-Ch	100	-	-	V	
		V _{GS} = 0 V, I _D = -250 μA	P-Ch	-100	-	-		
V _{DS} temperature coefficient	ΔV _{DS} /T _J	I _D = 250 μA	N-Ch	-	79	-	mV/°C	
		I _D = -250 μA	P-Ch	-	-68	-		
V _{GS(th)} temperature coefficient	ΔV _{GS(th)} /T _J	I _D = 250 μA	N-Ch	-	-4.4	-		
		I _D = -250 μA	P-Ch	-	4.3	-		
Gate threshold voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250 μA	N-Ch	1.5	-	2.5	V	
		V _{DS} = V _{GS} , I _D = -250 μA	P-Ch	-1.5	-	-2.5		
Gate-body leakage	I _{GSS}	V _{DS} = 0 V, V _{GS} = ± 20 V	N-Ch	-	-	± 100	nA	
			P-Ch	-	-	± 100		
Zero gate voltage drain current	I _{DSS}	V _{DS} = 100 V, V _{GS} = 0 V	N-Ch	-	-	1	μA	
		V _{DS} = -100 V, V _{GS} = 0 V	P-Ch	-	-	-1		
		V _{DS} = 100 V, V _{GS} = 0 V, T _J = 55 °C	N-Ch	-	-	10		
		V _{DS} = -100 V, V _{GS} = 0 V, T _J = 55 °C	P-Ch	-	-	-10		
On-state drain current ^b	I _{D(on)}	V _{DS} ≥ 5 V, V _{GS} = 10 V	N-Ch	4	-	-	A	
		V _{DS} ≤ -5 V, V _{GS} = -10 V	P-Ch	-4	-	-		
Drain-source on-state resistance ^b	R _{DS(on)}	V _{GS} = 10 V, I _D = 1.5 A	N-Ch	-	0.139	0.167	Ω	
		V _{GS} = -10 V, I _D = -2.3 A	P-Ch	-	0.197	0.251		
		V _{GS} = 4.5 V, I _D = 1.0 A	N-Ch	-	0.155	0.186		
		V _{GS} = -4.5 V, I _D = -2.0 A	P-Ch	-	0.260	0.338		
Forward transconductance ^b	g _{fs}	V _{DS} = 10 V, I _D = 2.7 A	N-Ch	-	10	-	S	
		V _{DS} = -10 V, I _D = 2.3 A	P-Ch	-	24	-		
Dynamic ^a								
Input capacitance	C _{iss}	N-channel V _{DS} = 50 V, V _{GS} = 0 V, f = 1 MHz P-channel V _{DS} = -50 V, V _{GS} = 0 V, f = 1 MHz	N-Ch	-	265	-	pF	
			P-Ch	-	325	-		
Output capacitance	C _{oss}		N-Ch	-	20	-		
			P-Ch	-	90	-		
Reverse transfer capacitance	C _{rss}		N-Ch	-	2	-		
			P-Ch	-	5	-		
Total gate charge	Q _g	V _{DS} = 50 V, V _{GS} = 10 V, I _D = 0.2 A	N-Ch	-	5.2	104	nC	
		V _{DS} = -50 V, V _{GS} = -10 V, I _D = -9 A	P-Ch	-	11.2	22.4		
		N-channel V _{DS} = 50 V, V _{GS} = 4.5 V, I _D = 0.2 A P-channel V _{DS} = -50 V, V _{GS} = -4.5 V, I _D = 2.3 A	N-Ch	-	2.4	4.8		
			P-Ch	-	5.7	11.4		
Gate-source charge	Q _{gs}		N-Ch	-	1.0	-		
			P-Ch	-	2.4	-		
Gate-drain charge	Q _{gd}		N-Ch	-	0.5	-		
			P-Ch	-	2.5	-		
Gate resistance	R _g	f = 1 MHz	N-Ch	0.24	1.2	2.4	Ω	
			P-Ch	0.76	3.8	7.6		









SPECIFICATIONS (T _J = 25 °C, unless otherwise noted)								
PARAMETER	SYMBOL	TEST CONDITIONS		MIN.	TYP.	MAX	UNIT	
Dynamic ^a								
Turn-on delay time	t _{d(on)}	N-channel V _{DD} = 10 V, R _L = 2 Ω I _D ≅ 2.1 A, V _{GEN} = 10 V, R _g = 1 Ω	N-Ch	-	12	25	ns	
			P-Ch	-	15	30		
Rise time	t _r		N-Ch	-	45	90		
			P-Ch	-	50	100		
Turn-off delay time	t _{d(off)}		N-Ch	-	22	45		
			P-Ch	-	30	60		
Fall time	t _f		N-Ch	-	12	25		
			P-Ch	-	11	20		
Turn-on delay time	t _{d(on)}	N-channel V _{DD} = 10 V, R _L = 2 Ω I _D ≅ 2.1 A, V _{GEN} = 4.5 V, R _g = 1 Ω	N-Ch	-	6	15		
			P-Ch	-	10	15		
Rise time	t _r		N-Ch	-	21	40		
			P-Ch	-	23	45		
Turn-off delay time	t _{d(off)}		N-Ch	-	20	40		
			P-Ch	-	26	50		
Fall time	t _f		N-Ch	-	10	20		
			P-Ch	-	10	20		
Drain-Source Body Diode Characteristics								
Continuous source-drain diode current	I _S	T _A = 25 °C	N-Ch	-	-	2.1	A	
			P-Ch	-	-	-2.2		
Pulse diode forward current (t = 100 μs)	I _{SM}		N-Ch	-	-	8		
			P-Ch	-	-	-10		
Body diode voltage	V _{SD}	I _S = 2.1 A, V _{GS} = 0 V	N-Ch	-	0.8	1.2	V	
		I _S = -1.8 A, V _{GS} = 0 V	P-Ch	-	-0.81	-1.2		
Body diode reverse recovery time	t _{rr}	N-channel I _F = -1.8 A, dI/dt = 100 A/μs, T _J = 25 °C	N-Ch	-	23	46	ns	
			P-Ch	-	37	74		
Body diode reverse recovery charge	Q _{rr}		N-Ch	-	21	42	nC	
			P-Ch	-	65	130		
Reverse recovery fall time	t _a		P-channel I _F = -1.8 A, dI/dt = -100 A/μs, T _J = 25 °C	N-Ch	-	21	-	ns
				P-Ch	-	34	-	
Reverse recovery rise time	t _b			N-Ch	-	2	-	
				P-Ch	-	3	-	

Notes


- a. Guaranteed by design, not subject to production testing.
b. Pulse test; pulse width $\leq 300\text{ }\mu\text{s}$, duty cycle $\leq 2\%$.

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.


N-CHANNEL TYPICAL CHARACTERISTICS (25 °C, unless otherwise noted)

Output Characteristics

Transfer Characteristics

On-Resistance vs. Drain Current and Gate Voltage

Capacitance

Gate Charge

On-Resistance vs. Junction Temperature




N-CHANNEL TYPICAL CHARACTERISTICS (25 °C, unless otherwise noted)




Source-Drain Diode Forward Voltage




On-Resistance vs. Gate-to-Source Voltage



Threshold Voltage






Single Pulse Power (Junction-to-Ambient)



Safe Operating Area, Junction-to-Ambient

Note


a. $V_{GS} >$ minimum V_{GS} at which $R_{DS(on)}$ is specified

N-CHANNEL TYPICAL CHARACTERISTICS (25 °C, unless otherwise noted)

Current Derating ^a

Power Junction to Ambient

Power Junction to Case
Note


- a. The power dissipation P_D is based on T_J max. = 150 °C, using junction-to-case thermal resistance, and is more useful in settling the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.









N-CHANNEL TYPICAL CHARACTERISTICS (25 °C, unless otherwise noted)



Normalized Thermal Transient Impedance, Junction-to-Ambient




Normalized Thermal Transient Impedance, Junction-to-Case


P-CHANNEL TYPICAL CHARACTERISTICS (25 °C, unless otherwise noted)

Output Characteristics

Transfer Characteristics

On-Resistance vs. Drain Current and Gate Voltage

Capacitance

Gate Charge

On-Resistance vs. Junction Temperature




P-CHANNEL TYPICAL CHARACTERISTICS (25 °C, unless otherwise noted)




Source-Drain Diode Forward Voltage




On-Resistance vs. Gate-to-Source Voltage



Threshold Voltage






Single Pulse Power, Junction-to-Ambient





Safe Operating Area, Junction-to-Ambient

Note

a. $V_{GS} >$ minimum V_{GS} at which $R_{DS(on)}$ is specified

P-CHANNEL TYPICAL CHARACTERISTICS (25 °C, unless otherwise noted)

Current Derating ^a

Power Junction to Ambient

Power Junction to Case
Note




- a. The power dissipation P_D is based on T_J max. = 150 °C, using junction-to-case thermal resistance, and is more useful in settling the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.

P-CHANNEL TYPICAL CHARACTERISTICS (25 °C, unless otherwise noted)

Normalized Thermal Transient Impedance, Junction-to-Ambient

Normalized Thermal Transient Impedance, Junction-to-Case


Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package / tape drawings, part marking, and reliability data, see www.vishay.com/ppg?63046.



PowerPAK® 1212-8, (Single / Dual)



Backside view of single pad



Backside view of dual pad

Notes

1. Inch will govern


[2] Dimensions exclusive of mold gate burrs

3. Dimensions exclusive of mold flash and cutting burrs


DIM.	MILLIMETERS			INCHES		
	MIN.	NOM.	MAX.	MIN.	NOM.	MAX.
A	0.97	1.04	1.12	0.038	0.041	0.044
A1	0.00	-	0.05	0.000	-	0.002
b	0.23	0.30	0.41	0.009	0.012	0.016
c	0.23	0.28	0.33	0.009	0.011	0.013
D	3.20	3.30	3.40	0.126	0.130	0.134
D1	2.95	3.05	3.15	0.116	0.120	0.124
D2	1.98	2.11	2.24	0.078	0.083	0.088
D3	0.48	-	0.89	0.019	-	0.035
D4	0.47 typ.			0.0185 typ		
D5	2.3 typ.			0.090 typ		
E	3.20	3.30	3.40	0.126	0.130	0.134
E1	2.95	3.05	3.15	0.116	0.120	0.124
E2	1.47	1.60	1.73	0.058	0.063	0.068
E3	1.75	1.85	1.98	0.069	0.073	0.078
E4	0.034 typ.			0.013 typ.		
e	0.65 BSC			0.026 BSC		
K	0.86 typ.			0.034 typ.		
K1	0.35	-	-	0.014	-	-
H	0.30	0.41	0.51	0.012	0.016	0.020
L	0.30	0.43	0.56	0.012	0.017	0.022
L1	0.06	0.13	0.20	0.002	0.005	0.008
θ	0°	-	12°	0°	-	12°
W	0.15	0.25	0.36	0.006	0.010	0.014
M	0.125 typ.			0.005 typ.		
ECN: S16-2667-Rev. M, 09-Jan-17						
DWG: 5882						




Recommended Land Pattern for PowerPAK® 1212-8 Dual



For BW package



For BWL package





Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.